


**EXTREME®** SELF LIGHTING TORCH KITS

Extreme Swirl Technology delivers high heat, super fast, reducing brazing time and fuel consumption. All air acetylene kits include gauge guards and cylinder wrench. Our best line of self-lighting torch kits are available in either valve rear or valve forward configurations. Improved design features quick-disconnect handles and replaceable tips and color coded "O" rings for quick gas identification.



AIR ACETYLENE



**PL-5ADLX-MC**  
**Torch Kit**  
**Part No. 0386-0832**

- Kit Includes:**
- AR-MC (CGA 200) Regulator
  - G-4 Handle
  - AH-12 Hose
  - PL-5A Tip
  - Soft solders to 1½" (38 mm)
  - Silver brazes to ¾" (19 mm)
  - "MC" Tank Connections
  - Instruction Manual



Kit No.	Part No.	Soft Solders	Silver Brazes	Regulator	Handle	Hose	Tip	Tank Connection	Valve Position
PL-5ADLX-MC	0386-0832	1½" (38 mm)	¾" (19 mm)	AR-MC (CGA-200)	G4	AH-12	PL-5A	MC	Rear
PL-5ADLX-B	0386-0833	1½" (38 mm)	¾" (19 mm)	AR-B (CGA-520)	G4	AH-12	PL-5A	B	Rear
PL-8ADLX-MC	0386-0834	2" (50 mm)	1" (25 mm)	AR-MC (CGA-200)	G4	AH-12	PL-8A	MC	Rear
PL-8ADLX-B	0386-0835	2" (50 mm)	1" (25 mm)	AR-B (CGA-520)	G4	AH-12	PL-8A	B	Rear
PL-12ADLX-B	0386-0836	4" (102 mm)	2" (50 mm)	AR-B (CGA-520)	G4	AH-12	PL-12A	B	Rear
PLF-5ADLX-MC	0386-0864	1½" (38 mm)	¾" (19 mm)	AR-MC (CGA-200)	PLF-A5	AH-12	PL-5A	MC	Forward
PLF-5ADLX-B	0386-0865	1½" (38 mm)	¾" (19 mm)	AR-B (CGA-520)	PLF-A5	AH-12	PL-5A	B	Forward
PLF-8ADLX-MC	0386-0866	2" (50 mm)	1" (25 mm)	AR-MC (CGA-200)	PLF-A5	AH-12	PL-8A	MC	Forward
PLF-8ADLX-B	0386-0867	2" (50 mm)	1" (25 mm)	AR-B (CGA-520)	PLF-A5	AH-12	PL-8A	B	Forward
PLF-12ADLX-B	0386-0868	4" (102 mm)	2" (50 mm)	AR-B (CGA-520)	PLF-A5	AH-12	PL-12A	B	Forward
PL-12ASTD	0386-0828	4" (102 mm)	2" (50 mm)	-	G4	-	PL-12A	-	Rear



# EXTREME® SELF LIGHTING REPLACEMENT TIPS

Increase the range of your torch kit with additional self lighting tips. All TurboTorch® tips feature an orifice screw that can be easily removed for simple cleaning or replacement, extending the life of the tip.



AIR ACETYLENE



**PL-3A**  
Replacement Tip  
Part No. 0386-0874



**PL-5A**  
Replacement Tip  
Part No. 0386-0818



**PL-8A**  
Replacement Tip  
Part No. 0386-0819



**PL-12A**  
Replacement Tip  
Part No. 0386-0820



**3A-TE**  
Replacement Tip End  
Part No. 0386-1059



**5A-TE**  
Replacement Tip End  
Part No. 0386-1064



**8A-TE**  
Replacement Tip End  
Part No. 0386-1065



**12A-TE**  
Replacement Tip End  
Part No. 0386-1066

Tip No.	Tip Part No.	Tip Size	Soft Solders	Silver Brazes	Gas Flow		Replacement Orifice	Replacement Tip End	BTU
					@14 PSI SCFH	(0.9 BAR) M3/HR			
PL-3A	0386-0874	3/16" (4.8 mm)	1/4" – 1" (6.4 – 25 mm)	1/8" – 1/2" (3.2 – 13 mm)	3.6	0.108	OR-A3 0386-1001	3A-TE 0386-1059	1,280
PL-5A	0386-0818	1/4" (6.4 mm)	3/4" – 1½" (19 – 38 mm)	1/4" – 3/4" (6.4 – 9.5 mm)	5	0.15	OR-A8 0386-1003	5A-TE 0386-1064	2,080
PL-8A	0386-0819	5/16" (7.9 mm)	1" – 2" (25 – 50 mm)	1/2" – 1" (13 – 25 mm)	7	0.21	– 0305-0511	8A-TE 0386-1065	2,520
PL-12A	0386-0820	3/8" (9.5 mm)	2" – 4" (50 – 102 mm)	1" – 2" (25 – 50 mm)	9	0.27	OR-T-6 0386-1024	12A-TE 0386-1066	3,360