

Accessories and Lenses

| | |
|-----------------------------|---|
| Supplied Accessories | Remote control, power cord, AA batteries x 2, RGB cable |
| Replacement Parts | |
| Remote Control | HL03171 |

Projection Throw Chart

| Screen Size | 16:10 | Throw Distance | |
|-------------|-------|----------------|-------|
| | | Diagonal | Width |
| 60 | 51 | 59 | 97 |
| 80 | 68 | 78 | 129 |
| 100 | 85 | 98 | 162 |
| 120 | 102 | 117 | 194 |
| 150 | 127 | 146 | 241 |
| 200 | 170 | 196 | 323 |
| 250 | 212 | 244 | 403 |
| 300 | 254 | 292 | 483 |

Throw Ratio: 1.15 - 1.9 : 1 (distance : width)
Screen size and throw distance are measured in inches.

Specifications

| | | |
|--------------------------|---------------------------------------|---|
| Display | Projection Technology | Single Chip DLP |
| | Resolution | WUXGA 1920 x 1200 |
| | Brightness | 5,000 ANSI lumens |
| | Colors | 1.07 billion colors |
| | Aspect Ratio | Native 16:10. 4:3 and 16:9 compatible |
| | Contrast Ratio | 20,000 : 1 |
| | Throw Ratio (distance : width) | 1.15 -1.9 : 1 |
| Operation | Focus Distance | 59" - 196" |
| | Display Size | 36.7" - 201.9" |
| | Lens | Manual zoom x 1.65, manual focus & lens shift |
| | Expected Light Source Life* | Approximately 20,000 hours |
| Compatibility | Speaker Output | 10W |
| | Keystone | H: +/-25° and V: +/-30° |
| | Computer | VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+, UXGA, WUXGA, MAC16", 480p, 576i, 576p, 720p, 1080i, 1080p |
| | H-Sync | 15.0 kHz - 91 kHz |
| | V-Sync | 24 Hz - 85 Hz |
| | Composite Video | NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM |
| | Component Video | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Connectors | HDMI | 480p, 576p, 720p, 1080i, 1080p Computer signal TMDS clock 27 MHz - 162 MHz |
| | MHL | 480p, 720p, 1080i, 1080p Computer signal TMDS clock 27 MHz - 162 MHz |
| | Digital Input | HDBaseT x 1, HDMI x 3 |
| | Computer Input 1 | 15-pin mini D-sub x 1 (shared with analog component video input) |
| | Computer Monitor Output | 15-pin mini D-sub x 1 |
| | Video Input | |
| | Composite Video | RCA jack x 1 |
| | Component Video | 15-pin mini D-sub x 1 (shared with analog computer input) |
| | Audio Input | 3.5 mm stereo mini jack x 1, 2RCA jack (L/R) x 1 |
| | Audio Output | 2RCA jack (L/R) x 1 |
| | Microphone Input | 3.5 mm mono mini jack |
| | Network (LAN) Wired | RJ-45 jack x 1 |
| | HDBaseT | RJ-45 jack x 1 |
| USB-A | USB type A x 1 | |
| Control Terminals | 9-pin D-sub x 1 (RS-232 control) | |
| 3D Sync | Mini DIN 3-pin connector x 1 | |
| Ratings & Warranty | Power Supply | AC 100V - 130V (50/60Hz) , 5.0A AC 200V - 240V (50/60Hz) , 2.5A |
| | Power Consumption | Normal: 460W |
| | Operating Temperature | 32°F - 95°F (0°C-35°C) Normal mode 32°F - 104° (0°C-40°C) Eco mode |
| | Dimensions (W x D x H) | 14.2" x 17.2" x 5.8" (excluding protruding parts) Shipping 19" x 21" x 9" |
| | Weight | Approximately 23.1 lbs. / Shipping 30 lbs. |
| | Approvals | UL 60950-1 / cUL FCC Part 15 subpart B class A |
| | Warranty | Five (5) year limited warranty plus Dukane's 1 year Peace of Mind Loaner Program |
| | UPC | 605194006670 |

* Actual light source life will vary by individual light source based on environmental conditions, selected operating mode, user settings and usage. Hours of average light source life specified are not guaranteed and do not constitute part of the product or light source warranty. Light source brightness decreases over time.



DUKANE CORP

Audio Visual Products
2900 Dukane Drive, St. Charles, Illinois 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukaneav.com

