

XG2 Series Industrial Grade In-Line GFCIs



XG2-14-2S

XG2-12-2TT

XG2-12-2W-15

XG2-12-2B

XG2-12-2W-UGP15231

* Each XG2 GFCI available in 2', 10', 25', 50' lengths




Standard Features:

- cULus listed for use in U.S. and Canada.
- Work site open-neutral protection compliant
- Enhanced immunity to nuisance tripping
- Fully sealed NEMA 6P submersible enclosure
- NEMA 4X and 6P configurations
- Rugged, impact resistant construction
- 15A and 20A models available
- 1.5 HP switch rating
- Immune to corrosive environments
- Superior strain relief
- Automatic and manual power-up options available
- Oversized test and reset buttons
- Hazardous location plugs are available as facility adapters
- Wide variety of plugs, connectors, and outlet receptacles

Applications:

- Equipment Protection
- Wet Location Environments
- Commercial Construction
- Industrial Construction
- Original Equipment Manufacturer
- Power Generation
- Oil & Gas

Dimensions:



Primary and Secondary Attachments:



Perma-Tite®

Perma-Grip™

SmartMonitor®

6000 Box

6100 Box

Explosion Proof Plug

Explosion Proof 30A Pin Plug



1.800.ERICSON · ericson.com · info@ericson.com



Selection Guide:

Part Number	Power Up Type	Length (ft.)	Primary	Secondary	Amps	Watts	NEMA Rating
XG2R-12-2BS-15	Auto	2 ft.	Molded NEMA 5-15	Blunt	15*	1800	NEMA 6P (Housing only)
XG2-14-2S	Auto	2 ft.	Molded NEMA 5-15	Molded NEMA 5-15	15	1800	NEMA 6P (Housing only)
XG2-14-25S	Auto	25 ft.	Molded NEMA 5-15	Molded NEMA 5-15	15	1800	NEMA 6P (Housing only)
XG2-12-2TT	Auto	2 ft.	Molded NEMA 5-15	Molded NEMA 5-15 Tri-tap	15	1800	NEMA 6P (Housing only)
XG2-12-50TT	Auto	50 ft.	Molded NEMA 5-15	Molded NEMA 5-15 Tri-tap	15	1800	NEMA 6P (Housing only)
XG2-12-2W	Auto	2 ft.	NEMA 5-20 1512-PW6P	NEMA 5-20 1612-CW6P	20	2400	NEMA 6P
XG2-12-2W-15	Auto	2 ft.	NEMA 5-15 1510-PW6P	NEMA 5-15 1610-CW6P	15	1800	NEMA 6P
XG2-12-2B	Auto	2 ft.	NEMA 5-20 1512-PG	6000 Outlet box, (2) 5-20 Duplex receptacles	20	2400	NEMA 6P (Housing only)
XG2-12-2BW	Auto	2 ft.	NEMA 5-20 1512-PW6P	6100 Outlet box, (2) 5-20 Duplex receptacles	20	2400	NEMA 6P (Housing only)
XG2-12-50BW	Auto	50 ft.	NEMA 5-20 1512-PW6P	6100 Outlet box, (2) 5-20 Duplex receptacles	20	2400	NEMA 6P (Housing only)
XG2-12-2BW-15	Auto	2 ft.	Nema 5-15 1510-PW6P	6100 Outlet box, (2) 5-15 Duplex receptacles	15	1875	NEMA 6P (Housing only)
XG2-12-50BW-15	Auto	2 ft.	Nema 5-15 1510-PW6P	6100 Outlet box, (2) 5-15 Duplex receptacles	15	1875	NEMA 6P (Housing only)
XG2-12-2BW-15-UGP15231	Auto	2 ft.	UGP15231 XP-Plug	6100 Outlet box, (2) NEMA 5-20R receptacles	15	1800	NEMA 6P (Housing only)
XG2-12-2TT-UGP15231	Auto	2 ft.	UGP15231 XP-Plug	Molded NEMA 5-15 Tri-tap	15	1800	NEMA 6P (Housing only)
XG2-12-2W-15-UGP15231	Auto	2 ft.	UGP15231 XP-Plug	NEMA 5-15 1610-CW6P	15	1800	NEMA 6P (Housing only)
XG2-12-2W-MR-15-UGP15231	Manual	2 ft.	UGP15231 XP-Plug	NEMA 5-15 1610-CW6P	15	1800	NEMA 6P (Housing only)
XG2-12-2W-UGP20231	Auto	2 ft.	UGP20231 XP-Plug	NEMA 5-20 1612-CW6P	20	2400	NEMA 6P (Housing only)
XG2-12-4W-CPH-3023BC	Auto	4 ft.	CPH-3023BC XP-Plug	NEMA 5-20 1612-CW6P	20	2400	NEMA 6P (Housing only)
XG2-12-4W-MR-CPH-3023BC	Manual	4 ft.	CPH-3023BC XP-Plug	NEMA 5-20 1612-CW6P	20	2400	NEMA 6P (Housing only)

*-Due to plug rating, plug can be removed. Unit rated for 20A max.



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1.800.374.2766
info@ericson.com
www.ericson.com
L1000829A