

Specifications	Range	Max Resolution	Basic Accuracy
Display		9999 count (backlit LCD)	
Foot-Candle (Fc)	0 to 9999 Fc	1 Fc	±4% rdg
	≥10,000 Fc	10 Fc	±5% rdg
Lux	0 to 9999 Lux	1 Lux	±4% rdg
	≥10000 Lux	10 Lux	±5% rdg
	≥100,000 Lux	100 Lux	±5% rdg
Sampling Rate		0.5 sec	
Connectivity		Bluetooth (Free ExView App)	
ExView App Compatibility		iOS 13.0 and higher & Android 9.0 and higher	
Transmission Distance		>10 m up to 90 m line of sight	
Power		3x AAA (1.5 V) battery (included)	
Operating Condition		0°C to 40°C (32°F to 104°F), ≤80% RH	
Dimensions/ Weight		6.9 × 2.1 × 1.1 in ( 176 × 53 × 28 mm) / 3.2 oz (90 g)	

## Extech Connected Environmental Meters

The Extech 250W Series includes 5 meters that are compatible with the ExView Mobile App: AN250W Anemometer, LT250W Light Meter, SL250W Sound Level Meter, RH250W Hygro-thermometer, and RPM250W Laser Tachometer. Connect up to 8 meters of any combination to measure and trend various parameters to help accurately diagnose environmental conditions and rotating equipment.



## Ordering

LT250W..... Light Meter with Connectivity to ExView App

### Extech Connected 250W Series Additional Models

AN250W ..... Anemometer with Connectivity to ExView App

RH250W ..... Hygro-Thermometer with Connectivity to ExView App

RPM250W..... Laser Tachometer with Connectivity to ExView App

SL250W ..... Sound Level Meter with Connectivity to ExView App