





Symbols

Symbol	Description
	WARNING. RISK OF DANGER.
	WARNING. HAZARDOUS VOLTAGE. Risk of electric shock.
	Consult user documentation.
CAT II	Measurement Category II is applicable to test and measuring circuits connected directly to utilization points (socket outlets and similar points) of the low-voltage MAINS installation.
CE	Conforms to European Union directives.
	This product complies with the WEEE Directive marking requirements. The affixed label indicates that you must not discard this electrical/electronic product in domestic household waste. Product Category: With reference to the equipment types in the WEEE Directive Annex I, this product is classed as category 9 "Monitoring and Control Instrumentation" product. Do not dispose of this product as unsorted municipal waste.

Specifications

Safety	IEC 61010-1, IEC 61010-2-030
Ratings	CAT II 250 V, 1000 mA
Connectors	SAE J1772 socket (type 1), 5 pin circular female connector
Operating temperature	-4 °F to 104 °F (-20 °C to 40 °C)
Operating humidity	10 % to 85 % relative humidity non-condensing
Storage temperature	-4 °F to 122 °F (-20 °C to 50 °C)
Storage humidity	0 % to 85 % relative humidity non-condensing
Operating altitude	6561 ft (2000 m) max.
Length	Approx. 23.2 in (590 mm) including connectors
Weight	Approx. 1.2 lb (550 g)