

Selecting Your Right Vector Network Analyzer

Maximize your budget with rentals of Keysight test equipment

Keysight E5071C ENA users chose their platform because they needed the absolute best tool of its time for the job. But much has changed since then. Today's devices are becoming highly integrated, requiring more than S-parameter measurements. As device characterization demands more measurement types, higher frequencies, and tighter tolerances, you need to adapt to the current situation and future-proof against new challenges. Gain deeper confidence in your measurements wherever you are with proven hardware and advanced software.



Figure 1. E5081A ENA-X cuts test cycle time up to 50% by providing network analysis and EVM measurements on a single test setup.

Find the Model Tailored to Your Exact Needs

The E5081A ENA-X vector network analyzer (VNA) offers advanced integrated noise receivers, direct receiver access, and modulated distortion software on a single test setup, enabling component characterization under high power, complex modulation schemes up to 44 GHz. These features consolidate the design verification setup necessary to conduct reliable characterization, minimizing test cycle time.

The E5080B ENA VNA brings excellent performance up to 53 GHz and flexibility to a mid-range platform. It provides complete passive and active component characterization in a single instrument.

Keysight P50xxB Streamline Series network analyzers bring high-end performance of benchtop instruments into a compact form factor. It's easy to share these instruments between test locations to make the same measurements reliably.

The M980xA PXIe VNA is a completely independent VNA with 2-, 4- or 6-ports, and the modules are easily configured as a true multiport VNA. A VNA with up to 50-ports can be configured in a single chassis for multiport applications.



Figure 2. E5080B ENA provides key improvement in performance and advanced software applications. It is more than just a VNA upgrade over the E5071C – it's a workflow update



Figure 3. P50xxB with 2-, 4- or 6-ports is packaged in a compact chassis and controlled by an external computer.



Figure 4. M980xA PXI VNA meets the most demanding multiport challenges with a true multiport architecture.

Keysight trade-in

VNA key trade-in benefits



Stretch your budget with great
Keysight credits



Migrate to the latest technology
– sooner



Enhance your competitive edge

Performance Comparisons – ENA-X / ENA / Streamline Series VNA / PXI VNA vs. E5071C ENA

	E5081A ENA-X	E5080B ENA	P50xxB Streamline Series VNA	M980xA PXIe VNA	E5071C ENA
Specifications					
Min frequency	10 MHz	9 kHz / 100 kHz	9 kHz / 100 kHz	9 kHz / 100 kHz	9 kHz / 300 kHz
Max frequency	20 / 44 GHz	4.5 / 6.5 / 9 / 14 / 18 / 20 GHz 26.5 / 32 / 44 / 53 GHz	4.5 / 6.5 / 9 / 14 / 20 GHz 26.5 / 32 / 44 / 53 GHz	4.5 / 6.5 / 9 / 14 / 20 GHz 26.5 / 32 / 44 / 53 GHz	4.5 / 6.5 / 8.5 / 14 / 20 GHz
Number of ports	2 / 4	2 / 4	2 / 4 / 6	2 / 4 / 6	2 / 4
Number of configurable ports	2	0	0	0	0
Max number of ports for full calibration	4	4	12	66	4
Connector type	3.5-mm (m), 2.4-mm (m)	Type-N (f), 3.5-mm (m), 2.4-mm (m), 1.85-mm (m)	3.5-mm (f), 2.4-mm (f), 1.85-mm (f)	3.5-mm (f), 2.4-mm (f), 1.85-mm (f)	Type-N (f), 3.5-mm (m)
Dynamic range (10 Hz IFBW)	@ 4 GHz	143 dB (port 1 and 2)	140 dB	140 dB	123 dB
	@ 20 GHz	134 dB (port 1 and 2)	126 dB	126 dB	96 dB
Trace noise @ 4 GHz	0.0015 dBrms (10 kHz IFBW)	0.0015 dBrms (10 kHz IFBW)	0.0015 dBrms (10 kHz IFBW)	0.0015 dBrms (10 kHz IFBW)	0.003 dBrms (70 kHz IFBW)
Power sweep range	@ 4 GHz	-80 to 16 dBm (port 1 and 2)	-60 to 10 dBm	-60 to 10 dBm	-55 to 10 dBm
	@ 20 GHz	-80 to 11 dBm (port 1 and 2)	-60 to 4 dBm	-60 to 4 dBm	-25 to 0 dBm
IF bandwidth	1 Hz to 15 MHz	1 Hz to 15 MHz	1 Hz to 15 MHz	1 Hz to 15 MHz	10 Hz to 1.5 MHz
Typical performance					
Temperature stability @ 4 GHz	0.005 dB/deg.C	0.005 dB/deg.C	0.005 dB/deg.C	0.005 dB/deg.C	0.005 dB/deg.C
Cycle time (2-port cal, narrow span, 201 points)	2 ms (1 MHz IFBW)	2 ms (1 MHz IFBW)	2 ms (1 MHz IFBW)	2 ms (1 MHz IFBW)	9 ms (500 kHz IFBW)
Hardware features					
Display	12.1 inch touchscreen, WXGA	12.1 inch touchscreen, WXGA	Not applicable	Not applicable	10.4 inch touchscreen, XGA
Configurable test set	Yes (port 1 and 2)	No	No	No	No
Low noise receivers for noise figure measurements	Yes (port 1 and 2)	No	No	No	No
Upconverter for modulation distortion analysis	Yes	No	No	No	No
Internal pulse modulators	Yes	Yes	Yes	Yes	No
Internal pulse generators	Yes	Yes	Yes	Yes	No
Internal second source	Yes	Yes	Yes	No	No
High stability timebase	Yes	Yes	No	No	Yes
AUX ports for DC measurements	Yes	Yes	No	No	Yes
Internal DC sources	Yes	Yes	No	No	No
Internal bias tees	No	Yes	No	No	Yes
Display interface	DisplayPort and VGA	DisplayPort and VGA	No	No	VGA
I/O interface	USB/LAN/GPIB/Handler IO	USB/LAN/GPIB/Handler IO	No	USB	USB/LAN/GPIB/Handler IO

	E5081A ENA-X	E5080B ENA	P50xxB Streamline Series VNA	M980xA PXIe VNA	E5071C ENA
Application software					
Automatic fixture removal	Yes	Yes	Yes	Yes	No
Enhanced time domain analysis with TDR	Yes	Yes	Yes	Yes	Yes
Real-time S-parameter and power measurement uncertainty	Yes	Yes	Yes	Yes	No
Basic pulsed-RF measurements	Yes	Yes	Yes	Yes	No
Noise figure measurements	Yes (with low-noise receivers)	Yes (with standard receivers)	Yes (with standard receivers)	Yes (with standard receivers)	No
Impedance analysis	No	Yes	No	No	No
Modulation distortion analysis (ex. EVM, ACP)	Yes	No	No	Yes	No
Scalar mixer calibrated measurements	Yes	Yes	Yes	Yes	Yes
Vector mixer calibrated measurements (SMC + phase)	Yes	Yes	Yes	Yes	No
Embedded LO capability	Yes	Yes	Yes	Yes	No
Gain compression application	Yes	Yes	Yes	Yes	No
Intermodulation distortion (IMD) measurements	Yes	Yes	Yes	Yes	No
Source phase control	Yes	Yes	Yes	Yes	No
Differential and I/Q device measurements	Yes	Yes	Yes	Yes	No
Spectrum analysis	Yes	Yes	Yes	Yes	No
True-mode stimulus	Yes	Yes	Yes	Yes	No
Multiport calibrated measurements (n > 4)	No	No	Yes	Yes	No
Banded millimeter-wave network analysis	No	No	Yes	Yes	No
Transportable, USB, networking (floating) licenses	Yes	Yes	No	Yes	No
VNA simulator	Yes	Yes	Yes	Yes	No

Contact Keysight Premier Rental Partners to get a Quote Now!

Premier Rental Partners

Americas

- Electro Rent: <https://www.electrorent.com/us/manufacturers/keysight-technologies>
- TRS-RenTelco: <https://www.trsrentelco.com/keysight>

Europe, Middle East, India, and Africa

- Electro Rent: <https://www.electrorent.com/eu/manufacturers/keysight-technologies>
- TRS-RenTelco: <https://www.trsrentelco.com/keysight>

Asia Pacific

- Orix Rentec: <http://www.orixrentec.jp/index.html>
- SMFL Rental Company Limited: <http://www.smfl-r.co.jp/english>
- Yokogawa Rental & Lease: <http://www.yrl.com/index.html>
- Lotte Rental: <http://www.lotterental.com>
- CHrent: <https://www.chrent.com/>

Find a Premier or Authorized Rental Partner nearest you:

www.keysight.com/find/rentalpartners

More Information: www.keysight.com/find/vna

Keysight enables innovators to push the boundaries of engineering by quickly solving design, emulation, and test challenges to create the best product experiences. Start your innovation journey at www.keysight.com.



This information is subject to change without notice. © Keysight Technologies, 2023, Published in USA, May 23, 2023, 3123-1364.EN