

LOCTITE® UR 3371™

A RELIABLE, FLEXIBLE ADHESIVE.



When you need a flexible, high-strength adhesive, LOCTITE® UR 3371™ provides great adhesion and sag resistance for expansive areas.

LOCTITE® UR 3371™ is a one component moisture cure polyurethane adhesive, that is easy to dispense. The skin-over time of 40 minutes and high initial tack provides time to align large parts and keep them in place once assembled. It adheres to most materials, such as glass, aluminum, metal, wood and concrete, without the need of a primer. The cured adhesive is flexible, durable and environmentally resistant.

FEATURES OF LOCTITE® UR 3371™

One part moisture cure polyurethane
Conveniently packaged in 300 ml cartridge
& 20 oz. sausage pack

Handling Properties:

- Non-sag
- Easy to apply
- High initial tack
- 40 minute skin over time

Cured Properties:

- Colors
- Paintable
- Adheres without using a primer to most common substrates such as glass, aluminum, metal, wood and concrete
- Flexible
- Environmental resistance



LOCTITE UR 3371 PROPERTIES

PACK SIZE*	ITEM NUMBER	COLOR	CHEMISTRY	SAG RESISTANCE	SKIN OVER/ TACK FREE	TENSILE SHEAR STRENGTH	ELONGATION AT BREAK
300ml Cartridge	2799582 2799581	White Grey	Polyurethane	<2.5 mm	Skin Over = 40 minutes	320 psi	500%
20 oz. Sausage Pack	2795475	White			Tack Free = 50 – 70 minutes		

*Made to order drum and pail size available

RECOMMENDED DISPENSERS


**HD10 300 ML PNEUMATIC
CARTRIDGE DISPENSER**

IDH 1714379



**SOFT PRESS 20 OZ.
PNEUMATIC APPLICATOR**

IDH 250052

Henkel Corporation
Engineering Adhesives
www.next.henkel-adhesives.com

U.S.A.
Henkel Corporation
Engineering Adhesives
One Henkel Way
Rocky Hill, Connecticut 06067
Tel: 1.800.LOCTITE (562.8483)
Tel: 860.571.5100
Fax: 860.571.5465

Canada
Henkel Canada Corporation
Engineering Adhesives
2515 Meadowpine Blvd.
Mississauga, Ontario L5N 6C3
Tel: 1.800.263.5043 (within Canada)
Tel: 905.814.6511
Fax: 905.814.5391



Henkel Adhesive Technologies

