
## **2X2AMP-BT2S64** – Two Source, Amplified, 6.5", Drop Ceiling Speaker with Bluetooth on a 2X2 Tile – Four Speaker Package

Two Source, 6.5" Amplified Drop Ceiling Speaker with Bluetooth on a 2X2 tile and backcan assembly delivers up to 40 watts power directly to the speaker. Each powered speaker (2X2AMP-BT2S61) can drive three additional speakers (2X2IC6NA). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15 Volt DC Level 5 power supply included and optional Volume Controls are available. Available also in models without Bluetooth features.

Four Speaker assembly consisting of the following;

- One (1) each (2X2AMP-BT2S61) 6.5" amplified speaker with One (1) each Backcan enclosure and one (1) each 2X2 tile assembled.
- 2) One (1) each UL Listed, Level 5, 15 VDC power supply (PS15VDC35AL5)
- 3) Three (3) each non-amplified Speaker on a 2X2 tile (2X2IC6NA)



## Features:

- Built onto the OWI IC6 In-Ceiling Speakers on a 2X2 Tile and backcan assembly
- 2 Line Level Input/Sources
- Up to 40 Watts of Power right at the speaker
- With Priority Override Features
- Balanced Line Level Output
- Bluetooth Features
- With a 3.5 mm Stereo Jack Line Input
- 15 Volt DC power supply (UL Listed-Level 5) included
- · Protected from shorts and overheating
- · Lower Noise Feature
- Fast and easy install in the field
- Optional Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

## Available in the following complete install packages:

2X2AMP-BT2S61 - One Speaker Package 2X2AMP-BT2S61SVC - One Speaker Package

X2AMP-BT2S61SVC - One Speaker Package with Volume Control

2X2AMP-BT2S62 - Two Speaker Package

2X2AMP-BT2S62SVC - Two Speaker Package with Volume Control

2X2AMP-BT2S64SVC - Four Speaker Package with Volume Control