## AMP-BT2SIC51SVC – Two Source, 5.25" Amplified Drop Ceiling

## With Bluetooth - One Speaker Package with Volume Control

Two Source, 5.25", Amplified Drop Ceiling Speakers with Bluetooth features, deliver up to 40 watts power directly to the speaker. Each powered speaker (AMP-BT2SIC5) can drive three additional speakers (IC5). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15 Volt DC Level 5 power supply included. Volume control included.

One Speaker combination package consisting of the following:

- 1.) One (1) each (AMP-BT2SIC5) 5.25" amplified speaker with (PS15VDC35AL5) 15 volts Level 5 power supply
- 2.) One (1) each Backcan enclosure
- 3.) One (1) each 5TB tile bridge
- 4.) One (1) each Volume Control (AMPSTVCW)



## Features:

- · Built onto the OWI IC5 In-Ceiling Speakers
- UL Listed, Energy Star, Energy Verified
- 2 Line Level Input/Sources
- Up to 40 Watts or Power right at the speaker
- With Priority Override Feature
- Balanced Line level Output
- With Bluetooth Features
- With a 3.5 mm Jack Line Input
- 15 Volt DC power supply (UL rated-Level 5) included
- · Protected from shorts and overheating
- Lower Noise Feature
- · Fast and easy install in the field
- Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

## Available also in other complete install packages:

AMP-BT2SIC51	<ul> <li>Single speaker combination with tile bridge and backcans.</li> </ul>
AMP-BT2SIC52	- Two speaker combination with tile bridges and backcans.
AMP-BT2SIC52SVC	- Two speaker combination with tile bridges, backcans and volume control.
AMP-BT2SIC54	- Four speaker combination with tile bridges and backcans.
AMP-BT2SIC54SVC	- Four speaker combination with tile bridges, backcans and volume control.