

AMP-BT2SIC61SVC – Two Source, 6.5” Amplified Drop Ceiling

With Bluetooth - One Speaker Package with Volume Control

Two Source, 6.5”, Amplified Drop Ceiling Speakers with Bluetooth features, deliver up to 40 watts power directly to the speaker. Each powered speaker (AMP-BT2SIC6) can drive three additional speakers (IC6). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15 Volt DC Level 5 power supply included. Volume control included.

One Speaker combination package consisting of the following:

- 1.) One (1) each (AMP-BT2SIC6) 6.5" amplified speaker with (PS15VDC35AL5) 15 volts Level 5 power supply
- 2.) One (1) each Backcan enclosure
- 3.) One (1) each 6TB tile bridge
- 4.) One (1) each Volume Control (AMPSTVCW)



Features:

- Built onto the OWI IC6 In-Ceiling Speakers
- UL Listed, Energy Star, Energy Verified
- 2 Line Level Input/Sources
- Up to 40 Watts or Power – right at the speaker
- With Priority Override Feature
- Balanced Line level Output
- With Bluetooth Features
- With a 3.5 mm Jack Line Input
- 15 Volt DC power supply (UL rated-Level 5) included
- Protected from shorts and overheating
- Lower Noise Feature
- Fast and easy – install in the field
- Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

Available also in other complete install packages:

- | | |
|---------------------------------|----------------------------------------------------------------------------|
| AMP-BT2SIC61 | - Single speaker combination with tile bridge and backcans. |
| AMP-BT2SIC62 | - Two speaker combination with tile bridges and backcans. |
| AMP-BT2SIC62SVC | - Two speaker combination with tile bridges, backcans and volume control. |
| AMP-BT2SIC64 | - Four speaker combination with tile bridges and backcans. |
| AMP-BT2SIC64SVC | - Four speaker combination with tile bridges, backcans and volume control. |

