Specifications

| Display/image |
|--|
| Display technology |
| Resolution |
| Brightness |
| Contrast ratio |
| Native aspect ratio |
| Aspect ratio - compatible |
| Keystone correction - vertical |
| Has vertical auto keystone correction |
| Displayable colors (millions) |
| Horizontal scan rate |
| Vertical scan rate |
| Uniformity |
| Screen size |
| Lamp info |
| Light source type |
| LASER life |
| Optical |
| Throw ratio |
| Projection distance |
| Zoom |
| Zoom type |
| Focal length (mm) |
| Native offset |
| Connectivity |
| Connections |

General Noise level (typical) 30dB 32dB Noise level (max) PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D compatibility 3D Full 3D Security Security bar, Kensington Lock, Password protected interface **IP** rating IP6X OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finish, French, German, Greek, Hungarian, Indon, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 24/7 operation Yes 360° operation Yes Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count Watts per speaker 15W In the box AC power cord Remote control 2x AAA batteries Basic user manual Optional wireless models UHDCast Pro Networking LAN - control Yes Power Power supply 100V ~ 240V, 50-60Hz Power consumption (standby) <0.5W Power consumption (min) 138W Power consumption (max) 161W Weight and dimensions Dimensions (W x D x H) 13.27" x 10.43" x 4.82" Gross weight 13.67 lbs Net weight 8.82 lbs

DLPTM WXGA (1280x800) 3,500 lumens 300,000:1 16:10 4:3,16:9 +/-40° Yes 1073.4

75%

Laser 30,000 hours 1.18:1 ~ 1.54:1 39.37" - 303.15" 1.3 Manual 16.901 ~ 21.6076 113%

15.375 ~ 91.146 Khz 50 ~ 85 Hz (120Hz for 3D)Hz

30.1" ~ 301" diagonal

x Audio 3.5mm

Inputs 2 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A **Control** 1 x RS232, 1 x RJ45, 1 x micro USB service







Copyright © 2021 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 02092021040352