

QUALITY TOOLS THAT GO TO WORK WITH YOU®



HUMM-VAC®

VACUUM PUMPS • 2 STAGE

FOR DEEP VACUUM

NEW & IMPROVED

CENTER BALANCED HANDLE WITH NON-SLIP GRIP

GAS BALLAST



DUAL VOLTAGE
110/220V – 50/60Hz
POWER BOX

OIL FILL PORT AND EXHAUST DOME

INTAKE FITTINGS WITH TETHERED CAPS AND CHECK VALVE



LARGE SIGHT GLASS FOR EASY OIL MONITORING



ANGLED OIL DRAIN FOR FASTER AND COMPLETE OIL DRAINAGE



HEAT DISPERSING MOTOR FINS



POWERFUL LOW DECIBEL FAN COOLED MOTOR

HEAT DISPERSING RESERVOIR FINS



WIDE, STABLE STEEL BASE
SURE-GRIP RUBBER FOOT PADS



UNIWELD® PRODUCTS, INC.
FT. LAUDERDALE, FL 33312 U.S.A.
www.uniweld.com





HUMM•VAC®

VACUUM PUMPS • 2 STAGE FOR DEEP VACUUM

NEW
&
IMPROVED



HVP12

HVP8

HVP6



Uniweld's Humm-Vac® 2-stage vacuum pumps feature a new and improved rotary vane vacuum pump cartridge that has the power and capacity needed for a wide range of service applications as well as robust construction for a long service life.

- Gas Ballast design mixes moisture laden air passing through pump with relatively dry air so compression doesn't cause condensation for prolong use of vacuum pump oil.
- Powerful dual voltage 110/220V – 50/60Hz thermally protected motor and factory rated to 15 microns for a fast, thorough evacuation.
- 1/4", 3/8", and 1/2" male flare intake fittings with tethered caps, and check valve, easy to read sight glass, easy access oil fill port, and angled oil drain valve for faster, more complete draining of the reservoir.
- Wide, stable steel base and sure grip rubber foot pads.

Pump Specifications	HVP6	HVP8	HVP12
Free Air Displacement	6.0 CFM, 170 liter/min.	8.0 CFM, 226 liter/min.	12.0 CFM, 340 liter/min.
Number of Stages	2-Stage Rotary Vane	2-Stage Rotary Vane	2-Stage Rotary Vane
Factory Micron Rating	15 Microns	15 Microns	15 Microns
Intake Fittings	1/4", 3/8" and 1/2" Male Flare	1/4", 3/8" and 1/2" Male Flare	1/4", 3/8" and 1/2" Male Flare
CE Motor with Thermal Overload Protection	1/2 HP	3/4 HP	1 HP
Voltage	110V – 50Hz 6.0 Amps/60Hz 5.5 Amps 220V – 50Hz 3.0 Amps/60Hz 2.8 Amps	110V – 50Hz 7.0 Amps/60Hz 6.7 Amps 220V – 50Hz 3.5 Amps/60Hz 3.3 Amps	110V – 50Hz 7.4 Amps/60Hz 7.6 Amps 220V – 50Hz 3.6 Amps/60Hz 3.8 Amps
Oil Capacity	27.1 oz. (800 ml)	25 oz. (740 ml)	33.8 oz. (1000 ml)
Power Cord U.S.–Type B Plug	72" (1.83m)	72" (1.83m)	72" (1.83m)
Dimensions	13.65" x 6.82" x 10.30" 34.66 cm x 17.32 cm x 26.15 cm	13.65" x 6.82" x 10.30" 34.66 cm x 17.32 cm x 26.15 cm	16.99" x 6.82" x 10.86" 43.15 cm x 17.32 cm x 27.58 cm
Weight	26.7 Lbs. (12.1 kg)	30.2 Lbs. (13.7 kg)	38.6 Lbs. (15.88 kg)
Shipping Weight	29.3 Lbs. (13.3 kg)	32.8 Lbs. (14.9 kg)	41.7 Lbs. (18.9 kg)
Color	Yellow	Red	Black

USE ONLY PREMIUM
UNIWELD VACUUM
PUMP OIL

- 42005 Quart (.946 liter) 12 per case
- 42006 Gallon (3.78 liters) 6 per case



UNIWELD® PRODUCTS, INC.
 2850 Ravenswood Road, Fort Lauderdale, FL 33312
 Customer Service: 800.323.2111 • 954.584.2000 • Fax: 954.587.0109
 www.uniweld.com • info@uniweld.com

U.S. PATENT #D0518068

SCAN FOR
PRODUCT
VIDEO



FY0053/1018