

ORDERING INFORMATION OPTIONS

Bezeichnung	Beschreibung	KB ECO 240	KB ECO 720	KB ECO 1020	Art.-Nr.
Access port with silicone plug	left				
	30 mm	•	•	•	8012-2113
	50 mm	•	•	•	8012-2120
	100 mm	•	•	•	8012-2118
	right				
	30 mm	•	•	•	8012-2112
	50 mm	•	•	•	8012-2119
	100 mm	•	•	•	8012-2117
	top				
	30 mm	•	•	•	8012-2114
	50 mm	•	•	•	8012-2115
	100 mm	•	•	•	8012-2116
Calibration certificate, expanded	for temperature; for extending the measurement in center of chamber to include another test temperature	•	•	•	8012-2107
Calibration certificate, temperature	for temperature, measurement in center of chamber at specified temperature	•	•	•	8012-2106
	temperature measurement incl. certificate and 27 measuring points at specified temperature	•	•	•	8012-2110
	temperature measurement incl. certificate, 15- 18 measuring points at specified temperature	•	•	•	8012-2109
	temperature measurement incl. certificate, 9 measuring points at specified temperature	•	•	•	8012-2108
Door lock	lockable door handle	•	–	–	8012-2121
		–	•	•	8012-2122

ORDERING INFORMATION ACCESSORIES

Bezeichnung	Beschreibung	KB ECO 240	KB ECO 720	KB ECO 1020	Art.-Nr.
APT-COM™ 4 BASIC-Edition	for simple logging and documentation requirements with up to 5 networked units. version 4, BASIC edition	•	•	•	9053-0039
APT-COM™ 4 GLP- Edition	for working under GLP-compliant conditions. Measured values are documented in a tamper-proof way in line with the requirements of FDA Regulation 21 CFR 11. version 4, GLP edition	•	•	•	9053-0042

Bezeichnung	Beschreibung	KB ECO 240	KB ECO 720	KB ECO 1020	Art.-Nr.
APT-COM™ 4 PROFESSIONAL-Edition	convenient unit and user management built on the BASIC edition. Suitable for networking up to 100 units.				
	version 4, PROFESSIONAL edition	•	•	•	9053-0040
LED light bars	Basic set consisting of 2 pieces, attachment material, control unit for max. 4 light strips, 100-240 V, 50/60 Hz				
	Basic set 300, length 30 cm	•	•	•	8012-1107
	Basic set 500, length 50 cm	•	•	•	8012-1108
	Basic set 900, length 90 cm	–	•	•	8012-1109
	Expansion set consisting of 2 pieces, attachment material: clips. For expanding the basic set of light bars				
	Expansion set 300, length 30 cm	•	•	•	8012-1716
	Expansion set 500, length 50 cm	•	•	•	8012-1717
	Expansion set 900, length 90 cm	–	•	•	8012-1718
pH-neutral detergent	concentrated, for gentle remove of residual contaminants; 1 kg	•	•	•	1002-0016
Qualification documents	IQ/OQ documents – supporting documents for validation performed by customers, consisting of: IQ/OQ checklists incl. calibration guide and comprehensive unit documentation; parameters: temperature and humidity values				
	Digital in PDF format	•	•	•	7057-0002
	Hard copy inside folder	•	•	•	7007-0002
	IQ/OQ/PQ documents – supporting documents for validation performed by customers, according to customer requirements, PQ section added to qualification folder IQ/OQ; parameters: temperature and humidity values				
	Digital in PDF format	•	•	•	7057-0006
	Hard copy inside folder	•	•	•	7007-0006
Rack	stainless steel	•	–	–	8012-2050
		–	•	–	8012-2051
		–	–	•	8012-2052
Rack, reinforced	stainless steel, with fasteners (1 set of 4)	•	–	–	8012-0638
		–	•	–	8012-0674
		–	–	•	8012-0968
		•	–	–	6004-0040
Shelf, perforated	Stainless steel	–	•	–	8009-0486
		–	–	•	8009-0792