LOCTITE.



Introducing the latest innovation from Henkel - a line of upgraded instant adhesives and accelerators that improve occupational safety through a reduction in hazardous chemicals.



THE CHALLENGE:

Several common ingredients used in instant adhesives and accelerators have come under greater regulatory scrutiny in select regions of the world.

THE SOLUTION:

In response to these regulatory concerns and the industrial market's demand, several Henkel formulations have been upgraded with more globally acceptable raw materials. This innovation combines upgraded formulations with the high quality and reliability for which the LOCTITE® brand is known.



UPGRADED FOR SAFETY. WITH UNCOMPROMISED PERFORMANCE.



INSTANT ADHESIVES - NEW AND IMPROVED

HQ- and MMBP-Free Formulations*





Instant Adhesive	Description or Key Feature	Pack Size	Item Number
403 TM	An ultra-performing, fast-setting instant adhesive that provides reliable performance under extreme operating temperatures up to 135°C.	20 gram	2714628
402™		500 gram	2712746
401™	A fast-setting, surface-insensitive, medium-viscosity instant adhesive that provides high shear strength on a wide range of materials.	20 gram	135429
		1 lb.	135430
40.CTM	A fast-setting, very-low viscosity instant adhesive that is ideal for small bondline gaps and close-fitting assemblies.	20 gram	135436
406™		1 lb.	237295
454™	A fast-setting, surface-insensitive, non-drip gel instant adhesive that is ideal for porous and vertical surfaces.	20 gram	135462
495™	A general purpose, low-viscosity instant adhesive that offers fast bonding on a wide range of materials.	20 gram	135467
3092™	A unique, two-part instant adhesive that provides gap filling in excess of 0.10" for a wide range of materials.	10 gram	1807961

^{*}HQ/MMBP-Free: These ingredients are no longer part of the LOCTITE® product formulas. Trace amounts are possible due to shared manufacturing processes and/or select raw material impurities. Hence, the Henkel specification level has been set at <50 PPM for HQ and <100 PPM for MMBP.



ACCELERATOR - IMPROVED

DMPT-Free Formulation**

Accelerator	Description or Key Feature	Pack Size	Item Number
SF 7452™	An accelerator for the increased cure speed of LOCTITE Instant Adhesives. It can be either pre- or post-applied.	1.75 fl. oz.	2765353

^{**}DMPT (N, N-dimethyl-p-toluidine) in 7452 has been replaced with Organic disulfide and/or Sulfenamide.

Consult the LOCTITE Technical Data Sheets for additional information.

Henkel Corporation Engineering Adhesives www.henkel-adhesives.com www.loctite.com



Scan to learn more.

Henkel Corporation

Engineering Adhesives One Henkel Wav

Rocky Hill, Connecticut 06067 Tel: 1.800.LOCTITE (562.8483)

Tel: 860.571.5100

Fax: 860.571.5465

Henkel Canada Corporation

Engineering Adhesives 2515 Meadowpine Blvd. Mississauga, Ontario L5N 6C3 Tel: 1.800.263.5043 (within Canada)

Tel: 905.814.6511 Fax: 905.814.5391

