

## ORDERING INFORMATION OPTIONS

Bezeichnung	Beschreibung	MK 56	MK 115	MK 240	MK 400	MK 720	MK 1020	Art.-Nr.
<b>Access port with silicone plug</b>	left							
	30 mm	•	•	•	•	•	•	8012-1322
	50 mm	•	•	•	•	•	•	8012-1328
	80 mm	•	•	•	•	•	•	8012-1334
	100 mm	–	•	•	•	•	•	8012-1542
	125 mm	–	•	•	•	•	•	8012-1351
	right							
	30 mm	•	•	•	•	•	•	8012-1319
	50 mm	•	•	•	•	•	•	8012-1325
	80 mm	•	•	•	•	•	•	8012-1331
	100 mm	–	•	•	•	•	•	8012-1539
	125 mm	–	•	•	•	•	•	8012-1348
	top							
	80 mm	•	•	•	•	•	•	8012-1536
	100 mm	–	•	•	•	•	•	8012-1530
125 mm	–	•	•	•	•	•	8012-1533	
<b>Analog output 4-20 mA</b>	for temperature values (output not adjustable)	•	•	•	•	•	•	8012-1084
<b>Calibration certificate, expanded</b>	for temperature; for extending the measurement in center of chamber to include another test temperature	•	•	•	•	•	•	8012-1124
<b>Calibration certificate, temperature</b>	for temperature, measurement in center of chamber at specified temperature	•	•	•	•	•	•	8012-1143
	temperature measurement incl. certificate and 27 measuring points at specified temperature	•	•	•	•	•	•	8012-1602
	temperature measurement incl. certificate, 15- 18 measuring points at specified temperature	•	•	•	•	•	•	8012-1581
	temperature measurement incl. certificate, 9 measuring points at specified temperature	•	•	•	•	•	•	8012-1560
<b>Compressed air connection</b>	for the connection to an existing pressurized air network	•	–	–	–	–	–	8012-1795
		–	•	–	–	–	–	8012-1801
		–	–	•	•	–	–	8012-1089
		–	–	–	–	•	•	8012-1797
<b>Door lock</b>	lockable door handle	•	–	–	–	–	–	8012-1782
		–	•	•	•	•	•	8012-1861

Bezeichnung	Beschreibung	MK 56	MK 115	MK 240	MK 400	MK 720	MK 1020	Art.-Nr.
<b>Dry-air purge</b>	uncontrolled, incl. connection; for preventing condensation	•	–	–	–	–	–	8012-1806
		–	•	–	–	–	–	8012-1087
		–	–	•	–	–	–	8012-1865
		–	–	–	–	•	–	8012-1866
<b>Notch-type access port</b>	notch-type access port in door, 100 x 35 mm	–	•	–	–	–	–	8012-1849
		–	–	•	•	–	–	8012-1850
		–	–	–	–	•	•	8012-1851
<b>Pt 100 temperature sensor</b>	additional flexible Pt 100, interior, for displaying the temperature on the unit display	•	•	•	•	•	•	8012-1093
<b>RS 485 interface, 2-wire</b>	Additional serial interface can be used parallel to Ethernet, for Multi Management Software APT-COM™	•	•	•	•	•	•	8012-1768
<b>Temperature safety device class 2</b>	with visual alarm (DIN 12880)	•	•	•	•	•	•	8012-1792
<b>Water cooling</b>	for reduced heat loss to ambient air	•	–	–	–	–	–	8012-1815
<b>Zero voltage relay contacts</b>	for controlling 3 relay contacts via program regulators, accessible via 6-pin DIN socket (max. 24 V - 2.5 A)	•	•	•	•	•	•	8012-1095

## ORDERING INFORMATION ACCESSORIES

Bezeichnung	Beschreibung	MK 56	MK 115	MK 240	MK 400	MK 720	MK 1020	Art.-Nr.
<b>Multi Management Software</b>	Multi Management Software APT-COM™							
	version 4, GLP edition	•	•	•	•	•	•	9053-0042
	version 4, PROFESSIONAL edition	•	•	•	•	•	•	9053-0040
<b>pH-neutral detergent</b>	concentrated, for gentle remove of residual contaminants; 1 kg	•	•	•	•	•	•	1002-0016
<b>Qualification documents</b>	IQ/OQ documents – supporting documents for validation performed by customers, consisting of: IQ/OQ checklists incl. calibration guide and comprehensive unit documentation; parameters: temperature, CO <sub>2</sub> , O <sub>2</sub> , pressure, depending on unit							
	Digital in PDF format	•	•	•	•	•	•	7057-0001
	Hard copy inside folder	•	•	•	•	•	•	7007-0001
	IQ/OQ/PQ documents – supporting documents for validation performed by customers, according to customer requirements, PQ section added to qualification folder IQ/OQ; parameters: temperature, CO <sub>2</sub> , O <sub>2</sub> – or pressure, depending on unit							
	Digital in PDF format	•	•	•	•	•	•	7057-0005
Hard copy inside folder	•	•	•	•	•	•	7007-0005	
<b>Rack</b>	stainless steel	•	–	–	–	–	–	8012-2085
		–	•	–	–	–	–	8012-2048
		–	–	•	–	–	–	8012-2053
		–	–	–	•	–	–	8012-2123
		–	–	–	–	•	–	8012-2054
		–	–	–	–	–	•	8012-2124
<b>Rack accessories</b>	fasteners (1 set of 4) for additional security of racks	•	•	•	•	•	•	8012-0620

Bezeichnung	Beschreibung	MK 56	MK 115	MK 240	MK 400	MK 720	MK 1020	Art.-Nr.
<b>Rack, reinforced</b>	stainless steel, with fasteners (1 set of 4)	•	–	–	–	–	–	8012-1091
		–	•	–	–	–	–	8012-0709
		–	–	•	–	–	–	8012-0605
		–	–	–	•	–	–	8012-2104
		–	–	–	–	•	–	8012-0684
		–	–	–	–	–	•	8012-2105
<b>RS 485 / RS 422 interface converter</b>	RS 422 cable set and RS 485 / RS 422 interface converter for connection to 10-way plug distributor							
	115 V option model	•	•	•	•	•	•	8012-0599
	230 V option model	•	•	•	•	•	•	8012-0589
<b>Shelf, perforated</b>	Stainless steel	•	–	–	–	–	–	6004-0182
		–	•	–	–	–	–	6004-0030
		–	–	•	–	–	–	8009-0447
		–	–	–	•	–	–	8009-1182
		–	–	–	–	•	–	8009-0511
		–	–	–	–	–	•	8009-1183
<b>Water supply set</b>	consisting of fresh- and waste-water containers (20 liters each), cabling and pump external, free-standing	•	–	–	–	–	–	8012-1846
<b>WLAN kit</b>	The kit contains a client bridge that establishes a wireless connection between BINDER units and APT-COM4, LIMS, or customer-specific software via an Ethernet interface. It provides an alternative solution in situations where units need to be positioned in locations without an on-site Ethernet connection. In secured networks, installation and configuration must be performed by the customer's IT service.	•	•	•	•	•	•	8500-0164