

ORDERING INFORMATION OPTIONS

Bezeichnung	Beschreibung	MKF 56	MKF 115	MKF 240	MKF 400	MKF 720	MKF 1020	Art.-Nr.
Access port with silicone plug	left							
	30 mm	•	•	•	•	•	•	8012-1323
	50 mm	•	•	•	•	•	•	8012-1329
	80 mm	•	•	•	•	•	•	8012-1335
	100 mm	–	•	•	•	•	•	8012-1543
	125 mm	–	•	•	•	•	•	8012-1352
	right							
	30 mm	•	•	•	•	•	•	8012-1320
	50 mm	•	•	•	•	•	•	8012-1326
	80 mm	•	•	•	•	•	•	8012-1332
	100 mm	–	•	•	•	•	•	8012-1540
	125 mm	–	•	•	•	•	•	8012-1349
	top							
	80 mm	•	•	•	•	•	•	8012-1537
	100 mm	–	•	•	•	•	•	8012-1531
125 mm	–	•	•	•	•	•	8012-1534	
Analog output 4-20 mA	for temperature and humidity values (output not adjustable)	•	•	•	•	•	•	8012-1085
Calibration certificate, expanded	for temperature and humidity; for extending the measurement in center of chamber to include another test value	•	•	•	•	•	•	8012-1194
Calibration certificate, temperature	temperature measurement incl. certificate and 27 measuring points at specified temperature	•	•	•	•	•	•	8012-1609
	temperature measurement incl. certificate, 15- 18 measuring points at specified temperature	•	•	•	•	•	•	8012-1589
	temperature measurement incl. certificate, 9 measuring points at specified temperature	•	•	•	•	•	•	8012-1568
Calibration certificate, temperature and humidity	Measurement in center of chamber at 25 °C / 60% RH or at specified test values	•	•	•	•	•	•	8012-1188
	temperature (according to DIN12880) and humidity measurement incl. certificate, 27 temperature measuring points and 1 humidity measuring point, at 25 °C / 60 % RH or at specified values	•	•	•	•	•	•	8012-1615
Compressed air connection		•	–	–	–	–	–	8012-1796
	for the connection to an existing pressurized air network	–	•	–	–	–	–	8012-1802
		–	–	•	•	–	–	8012-1787
		–	–	–	–	•	•	8012-1798
Door lock	lockable door handle	•	–	–	–	–	–	8012-1096
		–	•	•	•	•	•	8012-1862
Dry-air purge		•	–	–	–	–	–	8012-1088
	controlled, incl. connection; suitable for the simulation of current automobile industry standards	–	•	–	–	–	–	8012-1863
		–	–	•	–	–	–	8012-1869
		–	–	–	–	•	–	8012-1870
Notch-type access port		–	•	–	–	–	–	8012-1853
	notch-type access port in door, 100 x 35 mm	–	–	•	•	–	–	8012-1856
		–	–	–	–	•	•	8012-1859
Pt 100 temperature sensor	additional flexible Pt 100, interior, for displaying the temperature on the unit display	•	•	•	•	•	•	8012-1094
RS 485 interface, 2-wire	Additional serial interface can be used parallel to Ethernet, for Multi Management Software APT-COM™	•	•	•	•	•	•	8012-1769

Bezeichnung	Beschreibung	MKF 56	MKF 115	MKF 240	MKF 400	MKF 720	MKF 1020	Art.-Nr.
Temperature safety device class 2	with visual alarm (DIN 12880)	•	–	–	–	–	–	8012-1097
		–	•	•	•	•	•	8012-1864
Water circuit	allows condensed water to be reused	–	•	•	•	•	•	8012-1512
Water cooling	for reduced heat loss to ambient air	•	–	–	–	–	–	8012-1098
		–	•	–	–	–	–	8012-0843
		–	–	•	–	–	–	8012-0842
		–	–	–	–	•	–	8012-0804
		–	–	–	–	–	–	

ORDERING INFORMATION ACCESSORIES

Bezeichnung	Beschreibung	MKF 56	MKF 115	MKF 240	MKF 400	MKF 720	MKF 1020	Art.-Nr.
BINDER PURE AQUA SERVICE	System for preparation or complete desalination of tap water, complete set containing PURE AQUA 300 single-use cartridge, measuring device, and all necessary connecting parts	•	•	•	•	•	•	8012-0759
BINDER PURE AQUA SERVICE, accessories	Single-use, replacement cartridge for BINDER PURE AQUA System	•	•	•	•	•	•	6011-0165
Multi Management Software	Multi Management Software APT-COM™							
	version 4, GLP edition	•	•	•	•	•	•	9053-0042
	version 4, PROFESSIONAL edition	•	•	•	•	•	•	9053-0040
pH-neutral detergent	concentrated, for gentle remove of residual contaminants; 1 kg	•	•	•	•	•	•	1002-0016
Qualification documents	IQ/OQ documents – supporting documents for validation performed by customers, consisting of: IQ/OQ checklists incl. calibration guide and comprehensive unit documentation; parameters: temperature and humidity values							
	Digital in PDF format	•	•	•	•	•	•	7057-0002
	Hard copy inside folder	•	•	•	•	•	•	7007-0002
	IQ/OQ/PQ documents – supporting documents for validation performed by customers, according to customer requirements, PQ section added to qualification folder IQ/OQ; parameters: temperature and humidity values							
	Digital in PDF format	•	•	•	•	•	•	7057-0006
	Hard copy inside folder	•	•	•	•	•	•	7007-0006
Rack	stainless steel	•	–	–	–	–	–	8012-2085
		–	•	–	–	–	–	8012-2048
		–	–	•	–	–	–	8012-2053
		–	–	–	•	–	–	8012-2123
		–	–	–	–	•	–	8012-2054
		–	–	–	–	–	•	8012-2124
Rack accessories	fasteners (1 set of 4) for additional security of racks	•	•	•	•	•	•	8012-0620
Rack, reinforced	stainless steel, with fasteners (1 set of 4)	•	–	–	–	–	–	8012-1091
		–	•	–	–	–	–	8012-0709
		–	–	•	–	–	–	8012-0605
		–	–	–	•	–	–	8012-2104
		–	–	–	–	•	–	8012-0684
		–	–	–	–	–	•	8012-2105

Bezeichnung	Beschreibung	MKF 56	MKF 115	MKF 240	MKF 400	MKF 720	MKF 1020	Art.-Nr.
RS 485 / RS 422 interface converter	RS 422 cable set and RS 485 / RS 422 interface converter for connection to 10-way plug distributor							
	115 V option model	•	•	•	•	•	•	8012-0599
	230 V option model	•	•	•	•	•	•	8012-0589
Shelf, perforated	Stainless steel	•	–	–	–	–	–	6004-0182
		–	•	–	–	–	–	6004-0030
		–	–	•	–	–	–	8009-0447
		–	–	–	–	•	–	8009-0511
		–	–	–	–	–	•	8009-1183
Water supply set	consisting of fresh- and waste-water containers (20 liters each), cabling and pump external, free-standing	•	–	–	–	–	–	8012-1846
WLAN kit	The kit contains a client bridge that establishes a wireless connection between BINDER units and APT-COM4, LIMS, or customer-specific software via an Ethernet interface. It provides an alternative solu- tion in situations where units need to be positioned in locations without an on-site Ethernet connection. In secured networks, installation and configuration must be performed by the customer's IT service.	•	•	•	•	•	•	8500-0164