

INTELLIGENT REWORK EQUIPMENT

QUICK/8600A Lead Free Rework Station



Plug-in design of heater

Features

- Closed loop sensor, zero triggering, micro computer controls temperature, LED display, fast heating, precise and stable temperature not affected by air volume.
- Induction switch inside the handle. The unit starts working as soon as the handle is picked up and enter standby state when the handle is placed on the holder. Easy for real-time operation.
- Light handle
- Plug-in design of heating element, easy and convenient maintenance, types of nozzles optional.
- Digital temperature calibration, easy to use.
- Cooling air function available can prolong the lifetime of the heater and protect the unit.

Specifications

Power	120W
Display	LED (Resolution 1 °C)
Pump	Diaphragm
Air Flow	0.3~6.8L/min, Stepless adjustable
Noise	<60dB
Temperature Range	100°C~450°C
Heating Method	Ceramic heater
Dimensions	100 (W) x 210 (L) x 135 (H) mm
Weight	About 2.6kg

P/N	Specification
A1065	ø1.5mm (0.06in)
A1066	ø2.0mm (0.08in)
A1067	ø2.5mm (0.10in)
A1068	ø3.0mm (0.12in)
A1069	ø3.5mm (0.14in)
A1070	ø4.0mm (0.18in)



Standard nozzle