It's an **Emak S.p.A.** trademark 42011 Bagnolo in Piano (RE) Italy **www.myoleomac.com**

- www.youtube.com/MyOleoMac
- www.facebook.com/OleoMacItalia
- www.instagram.com/OleoMacItalia



NEW CHAINSAWS

GSH 51/GSH 510* | GSH 56/GSH 560*



The green of **Emak** is an assurance

of quality, innovation and completeness.

The green of **Emak** is a green produced with **care** and **respect**, **passion** and **design**.

Gardening, farming and forestry tools for home users and professionals. Emak covers all shades of green. With different models to meet each user's needs but all sharing the same exceptional quality standards in terms of performance, reliability, comfort and safety.

Our product range includes over **250 models** designed for all types of activity. Chain saws, brushcutters, lawnmowers, garden tractors, hedgetrimmers, rotary tillers, rotary cultivators, cutterbarmowers, transporters and much more besides, for jobs of varying intensity, power and frequency.

- 4 commercial brands
- 4 production units
- 8 branches (Germany, France, United Kingdom, Spain, Poland, Ukraine, China, Brazil)
- 135 distributors
- 85 countries covered
- 22.000 retail outlets served
- 22 product families

The world's first company in its sector to simultaneously hold **ISO 9001** Quality, **SA 8000** Ethical and **ISO 14001** Environmental accreditation.

A true Italian passion for over 50 years.

There's an **Emak** for everyone







SOLID





BRAND NEW AND DISTINCTIVE DESIGN

We are proud to introduce a new range of chainsaws, for hobby and farmer use, with exclusive design, best in class performances and durable features.



2





MAIN FEATURES



for a strong working capacity, even in tough conditions.

HIGH TORQUE, also at low idle, for faster working capacity and in stressful condition.

GOOD ACCELERATION,

for immediate response when power is needed.

LOWER WORKING TEMPERATURES,
to grant higher comfort, safety and engine durability over the time. (1)

LOWER VIBRATIONS,

thanks to the anti-vibration system, for higher working comfort. (2)

EASY MACHINE START,

to activate the machine in no time and be operative in any conditions.

■ LOW FUEL CONSUMPTION,

for low operating costs.

USE OF 2% MIX,

to grant better engine lubrication and high efficiency.

■ NICKEL PLATED CYLINDER,

for higher cylinder durability over time, better engine lubrication, better cylinder/piston match. (3)

CARBURATION STABILITY,

granting a smooth functioning of the machine. (4)





TECHNICAL FEATURES



	GSH 51	GSH 510*	GSH 56	GSH 560*
DISPLACEMENT	50.9 cm ³		54.5 cm ³	
POWER	3.0 HP (2.2 kW)		3.5 HP (2.6 kW)	
BAR TYPE	Oregon 18"		Oregon 20"	
CHAIN (PITCH)	Oregon .325" and 3/8"		Oregon .325" and 3/8"	
CARBURETTOR	Walbro		Walbro	
PRIMER	yes, Walbro		yes, Walbro	
CHAIN-TENSION SYSTEM	lateral		lateral	
FILTER	nylon		nylon	
FILTER COVER	"no tools" (knob)		"no tools" (knob)	
CRANKCASE	aluminum	magnesium	aluminum	magnesium
DRY WEIGHT (WITHOUT BAR AND CHAIN)	5.2 Kg	5.0 Kg	5.3 Kg	5.1 Kg
SAFETY	EU standards		EU standards	

*Euro 2 version, available for EU market

PROTECTIVE CLOTHING AND LUBRICANTS







Chain resistant forestry boots with rigid toecap



Leggings with anti-cut protection



PROSINT 2 special oil for 2-stroke engines



ECOLUBE biodegradeable oil for chains

For sound advice, just ask our authorized dealer.