




DIMENSIONAL DATA NESTING CHART

Earthwool® 1000° Pipe Insulation

DIMENSIONAL DATA NESTING CHART

Single Layer




INSULATION O.D. SINGLE LAYER DIMENSIONAL DATA												
Iron Pipe Size	Iron Pipe Outside Diameter	Insulation Wall Thickness										
		½"	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
½"	0.840"	1.900	2.820	3.950	4.950	—	—	—	—	—	—	—
¾"	1.050"	2.160	2.820	3.950	4.950	—	—	—	—	—	—	—
1"	1.315"	2.375	3.450	4.450	5.510	—	—	—	—	—	—	—
1¼"	1.660"	2.720	3.450	4.950	5.510	—	—	—	—	—	—	—
1½"	1.900"	2.875	3.950	4.950	6.570	—	—	—	—	—	—	—
2"	2.375"	3.420	4.450	5.510	6.570	7.570	8.570	9.570	10.700	11.750	12.700	13.950
2½"	2.875"	3.930	4.950	6.570	7.570	8.570	9.570	10.750	11.700	11.750	13.950	15.950
3"	3.500"	4.500	5.510	6.570	7.570	8.570	9.570	10.700	11.700	12.700	13.950	15.950
3½"	4.000"	5.000	6.570	7.570	8.570	9.570	10.700	11.700	12.700	12.700	13.950	15.950
4"	4.500"	5.563	6.570	7.570	8.570	9.570	10.700	11.700	12.700	13.950	14.950	16.950
4½"	5.000"	—	7.570	8.570	9.570	10.700	11.700	12.700	12.700	13.950	14.950	17.000
5"	5.563"	—	7.570	8.570	9.570	10.700	11.700	12.700	13.950	14.950	15.950	18.000
6"	6.625"	—	8.570	9.570	10.700	11.700	12.700	13.950	14.950	15.950	16.950	19.000
7"	7.625"	—	9.570	10.700	11.700	12.700	13.950	14.950	15.950	16.950	17.950	20.000
8"	8.625"	—	10.700	11.700	12.700	13.950	14.950	15.950	16.950	17.950	18.950	21.000
9"	9.625"	—	11.700	12.700	13.950	14.950	15.950	16.950	17.950	18.950	19.950	22.000
10"	10.750"	—	12.700	13.950	14.950	15.950	16.950	17.950	18.950	19.950	20.950	23.000
11"	11.750"	—	13.950	14.950	15.950	16.950	17.950	18.950	19.950	20.950	21.950	24.000
12"	12.750"	—	14.950	15.950	16.950	17.950	18.950	19.950	20.950	21.950	22.950	25.000
14"	14.000"	—	15.950	16.950	17.950	18.950	19.950	20.950	21.950	22.950	23.950	26.000
15"	15.000"	—	16.950	17.950	18.950	19.950	20.950	21.950	22.950	23.950	24.950	27.000
16"	16.000"	—	17.950	18.950	19.950	20.950	21.950	22.950	23.950	24.950	25.950	28.000
17"	17.000"	—	18.950	19.950	20.950	21.950	22.950	23.950	24.950	25.950	26.950	—
18"	18.000"	—	19.950	20.950	21.950	22.950	23.950	24.950	25.950	26.950	27.950	—
19"	19.000"	—	20.950	21.950	22.950	23.950	24.950	25.950	26.950	27.950	—	—
20"	20.000"	—	21.950	22.950	23.950	24.950	25.950	26.950	27.950	—	—	—
21"	21.000"	—	22.950	23.950	24.950	25.950	26.950	27.950	—	—	—	—
22"	22.000"	—	23.950	24.950	25.950	26.950	27.950	—	—	—	—	—
23"	23.000"	—	24.950	25.950	26.950	27.950	—	—	—	—	—	—
24"	24.000"	—	25.950	26.950	27.950	—	—	—	—	—	—	—

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards.

DIMENSIONAL DATA NESTING CHART

Single Layer




ACTUAL WALL THICKNESS SINGLE LAYER DIMENSIONAL DATA*

Iron Pipe Size	Iron Pipe Outside Diameter	Insulation Wall Thickness										
		½"	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
½"	0.840"	0.485	0.945	1.510	2.010	—	—	—	—	—	—	—
¾"	1.050"	0.495	0.825	1.390	1.890	—	—	—	—	—	—	—
1"	1.315"	0.478	1.015	1.515	2.045	—	—	—	—	—	—	—
1¼"	1.660"	0.515	0.880	1.630	1.910	—	—	—	—	—	—	—
1½"	1.900"	0.468	1.005	1.505	2.315	—	—	—	—	—	—	—
2"	2.375"	0.460	0.975	1.505	2.035	2.535	3.035	3.540	4.100	4.625	5.100	5.730
2½"	2.875"	0.465	0.975	1.785	2.285	2.785	3.285	3.850	4.350	4.375	5.480	6.480
3"	3.500"	0.460	0.965	1.495	1.995	2.495	2.995	3.560	4.060	4.560	5.190	6.190
3½"	4.000"	0.470	1.225	1.755	2.255	2.755	3.320	3.820	4.320	4.320	4.950	5.950
4"	4.500"	0.502	1.005	1.505	2.005	2.505	3.070	3.570	4.070	4.695	5.195	6.200
4½"	5.000"	—	1.225	1.755	2.255	2.820	3.320	3.820	3.820	4.445	4.945	5.950
5"	5.563"	—	0.950	1.455	1.950	2.515	3.015	3.515	4.140	4.640	5.140	6.140
6"	6.625"	—	0.920	1.420	1.985	2.485	2.985	3.610	4.110	4.610	5.110	6.110
7"	7.625"	—	0.920	1.485	1.985	2.485	3.110	3.610	4.110	4.610	5.110	6.110
8"	8.625"	—	0.970	1.470	1.970	2.595	3.095	3.595	4.095	4.600	5.095	6.100
9"	9.625"	—	0.990	1.490	2.115	2.615	3.115	3.615	4.115	4.615	5.115	6.120
10"	10.750"	—	0.905	1.530	2.030	2.530	3.030	3.530	4.030	4.545	5.030	6.030
11"	11.750"	—	1.045	1.545	2.045	2.545	3.045	3.545	4.045	4.545	5.045	6.050
12"	12.750"	—	1.035	1.535	2.035	2.535	3.035	3.535	4.035	4.535	5.035	6.040
14"	14.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	4.910	5.910
15"	15.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	4.910	5.910
16"	16.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	4.910	5.910
17"	17.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	4.910	—
18"	18.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	4.910	—
19"	19.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	4.410	—	—
20"	20.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	3.910	—	—	—
21"	21.000"	—	0.910	1.410	1.910	2.410	2.910	3.410	—	—	—	—
22"	22.000"	—	0.910	1.410	1.910	2.410	2.910	—	—	—	—	—
23"	23.000"	—	0.910	1.410	1.910	2.410	—	—	—	—	—	—
24"	24.000"	—	0.910	1.410	1.910	—	—	—	—	—	—	—

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards. *Subject to Knauf Insulation tolerances.

DIMENSIONAL DATA NESTING CHART

Double Layer



IRON PIPE DOUBLE LAYER NESTING CHART


Iron Pipe Size	Iron Pipe Outside Diameter	Insulation Wall Thickness									
		1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
½"	0.840"	½ x ½ 1½ x ½	½ x ½ 1½ x 1	½ x 1 2½ x 1	½ x 1 2½ x 1½	½ x 1½ 3½ x 1½	½ x 1½ 3½ x 2	½ x 2 4½ x 2	½ x 2 4½ x 2½	½ x 2 4½ x 3	½ x 2 4½ x 4
¾"	1.050"	¾ x ½ 2 x ½	¾ x ½ 2 x 1	¾ x 1 2½ x 1	¾ x 1 2½ x 1½	¾ x 1 2½ x 2	¾ x 1½ 3½ x 2	¾ x 2 4½ x 2	¾ x 2 4½ x 2½	¾ x 2 4½ x 3	¾ x 2 4½ x 4
1"	1.315"	1 x ½ 2 x ½	1 x ½ 2 x 1	1 x 1 3 x 1	1 x 1½ 4 x 1	1 x 1½ 4 x 1½	1 x 1½ 4 x 2	1 x 2 5 x 2	1 x 1½ 4 x 3	1 x 2 5 x 3	1 x 2 5 x 4
1¼"	1.660"	1¼ x ½ 2½ x ½	1¼ x ½ 2½ x 1	1¼ x 1 3 x 1	1¼ x 1 3 x 1½	1¼ x 1½ 4½ x 1½	1¼ x 1½ 4½ x 2	1¼ x 2 5 x 2	1¼ x 2 5 x 2½	1¼ x 2 5 x 3	1¼ x 2 5 x 4
1½"	1.900"	1½ x ½ 2½ x ½	1½ x ½ 2½ x 1	1½ x 1 3½ x 1	1½ x 1 3½ x 1½	1½ x 1½ 4½ x 1½	1½ x 1½ 4½ x 2	1½ x 2 6 x 2	1½ x 2 6 x 2½	1½ x 2 6 x 3	1½ x 2 6 x 4
2"	2.375"	2 x ½ 3 x ½	2 x ½ 3 x 1	2 x 1 4 x 1	2 x 1 4 x 1½	2 x 1½ 5 x 1½	2 x 2 6 x 1½	2 x 2 6 x 2	2 x 2 6 x 2½	2 x 2 6 x 3	2 x 3 8 x 3
2½"	2.875"	2½ x ½ 3½ x ½	2½ x ½ 3½ x 1	2½ x 1 4½ x 1	2½ x 1 4½ x 1½	2½ x 1½ 6½ x 1½	2½ x 1½ 6 x 2	2½ x 1½ 6 x 2½	2½ x 2 7 x 2½	2½ x 2 7 x 3	2½ x 3 9 x 3
3"	3.500"	3 x ½ 4 x ½	3 x ½ 4 x 1	3 x 1 5 x 1	3 x 1 5 x 1½	3 x 1½ 6 x 1½	3 x 1½ 6 x 2	3 x 1½ 6 x 2½	3 x 2 7 x 2½	3 x 2½ 8 x 2½	3 x 2½ 8 x 3½
3½"	4.000"	— —	3½ x ½ 4½ x 1	3½ x 1 6 x 1	3½ x 1 6 x 1½	3½ x 1½ 7 x 1½	3½ x 1½ 7 x 2	3½ x 2 8 x 2	3½ x 2 8 x 2½	3½ x 2 8 x 3	3½ x 2 8 x 4
4"	4.500"	— —	4 x ½ 5 x 1	4 x 1 6 x 1	4 x 1 6 x 1½	4 x 1 6 x 2	4 x 2 8 x 1½	4 x 2 8 x 2	4 x 2 8 x 2½	4 x 2 8 x 3	4 x 3 10 x 3
4½"	5.000"	— —	— —	4½ x 1 7 x 1	4½ x 1½ 8 x 1	4½ x 1½ 8 x 1½	4½ x 1½ 8 x 2	4½ x 1½ 8 x 2½	4½ x 2 9 x 2½	4½ x 2½ 10 x 2½	4½ x 3 11 x 3
5"	5.563"	— —	— —	5 x 1 7 x 1	5 x 1½ 8 x 1	5 x 1½ 8 x 1½	5 x 1½ 8 x 2	5 x 1½ 8 x 2½	5 x 2 9 x 2½	5 x 2½ 10 x 2½	5 x 2½ 10 x 3½
6"	6.625"	— —	— —	6 x 1 8 x 1	6 x 1 8 x 1½	6 x 1 8 x 2	6 x 2 10 x 1½	6 x 2 10 x 2	6 x 2 10 x 2½	6 x 2 10 x 3	6 x 3 12 x 3
7"	7.625"	— —	— —	7 x 1 9 x 1	7 x 1 9 x 1½	7 x 1½ 10 x 1½	7 x 1½ 10 x 2	7 x 2 11 x 2	7 x 2 11 x 2½	7 x 3 14 x 2	7 x 3 14 x 3
8"	8.625"	— —	— —	8 x 1 10 x 1	8 x 1 10 x 1½	8 x 1½ 11 x 1½	8 x 1½ 11 x 2	8 x 2 12 x 2	8 x 2 12 x 2½	8 x 2 12 x 3	8 x 3 15 x 3
9"	9.625"	— —	— —	9 x 1 11 x 1	9 x 1 11 x 1½	9 x 1½ 12 x 1½	9 x 1½ 12 x 2	9 x 2 14 x 2	9 x 2 14 x 2½	9 x 3 16 x 2	9 x 3 16 x 3
10"	10.750"	— —	— —	10 x 1 12 x 1	10 x 1 12 x 1½	10 x 1½ 14 x 1½	10 x 1½ 14 x 2	10 x 2 15 x 2	10 x 2 15 x 2½	10 x 2 15 x 3	10 x 3 17 x 3
11"	11.750"	— —	— —	11 x 1 14 x 1	11 x 1 14 x 1½	11 x 1½ 15 x 1½	11 x 1½ 15 x 2	11 x 2 16 x 2	11 x 2 16 x 2½	11 x 3 18 x 2	11 x 3 18 x 3
12"	12.750"	— —	— —	12 x 1 15 x 1	12 x 1 15 x 1½	12 x 1½ 16 x 1½	12 x 1½ 16 x 2	12 x 2 17 x 2	12 x 2 17 x 2½	12 x 3 19 x 2	12 x 3 19 x 3

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards.

These are suggested nesting combinations only. For other combinations choose an iron pipe size that equals the outside diameter of the insulation layer to be covered.

DIMENSIONAL DATA NESTING CHART

Double Layer



IRON PIPE DOUBLE LAYER NESTING CHART


Iron Pipe Size	Iron Pipe Outside Diameter	Insulation Wall Thickness									
		1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
14"	14.000"	— —	— —	14 x 1 16 x 1	14 x 1 16 x 1½	14 x 1½ 17 x 1½	14 x 1½ 17 x 2	14 x 2 18 x 2	14 x 2 18 x 2½	14 x 2 18 x 3	14 x 3 20 x 3
15"	15.000"	— —	— —	15 x 1 17 x 1	15 x 1 17 x 1½	15 x 1½ 18 x 1½	15 x 1½ 18 x 2	15 x 2 19 x 2	15 x 2 19 x 2½	15 x 3 21 x 2	15 x 3 21 x 3
16"	16.000"	— —	— —	16 x 1 18 x 1	16 x 1 18 x 1½	16 x 1½ 19 x 1½	16 x 1½ 19 x 2	16 x 2 20 x 2	16 x 2 20 x 2½	16 x 2 20 x 3	16 x 3 22 x 3
17"	17.000"	— —	— —	17 x 1 19 x 1	17 x 1 19 x 1½	17 x 1½ 20 x 1½	17 x 1½ 20 x 2	17 x 2 21 x 2	17 x 2 21 x 2½	17 x 3 23 x 2	— —
18"	18.000"	— —	— —	18 x 1 20 x 1	18 x 1 20 x 1½	18 x 1½ 21 x 1½	18 x 1½ 21 x 2	18 x 2 22 x 2	18 x 2 22 x 2½	— —	— —
19"	19.000"	— —	— —	19 x 1 21 x 1	19 x 1 21 x 1½	19 x 1½ 22 x 1½	19 x 1½ 22 x 2	19 x 2 23 x 2	19 x 2 23 x 2½	— —	— —
20"	20.000"	— —	— —	20 x 1 22 x 1	20 x 1 22 x 1½	20 x 1½ 23 x 1½	20 x 1½ 23 x 2	20 x 2 24 x 2	— —	— —	— —
21"	21.000"	— —	— —	21 x 1 23 x 1	21 x 1 23 x 1½	21 x 1½ 24 x 1½	21 x 1½ 24 x 2	— —	— —	— —	— —
22"	22.000"	— —	— —	22 x 1 24 x 1	22 x 1 24 x 1½	— —	— —	— —	— —	— —	— —
23"	23.000"	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —
24"	24.000"	— —	— —	— —	— —	— —	— —	— —	— —	— —	— —

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards.

These are suggested nesting combinations only. For other combinations choose an iron pipe size that equals the outside diameter of the insulation layer to be covered.

DIMENSIONAL DATA NESTING CHART

Copper Tube, Single Layer



COPPER TUBE INSULATION O.D. SINGLE LAYER DIMENSIONAL DATA

Copper Tube Size	Copper Tube Outside Diameter	Insulation Wall Thickness										
		½"	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
⅝"	0.625"	1.660	2.820	3.450	4.500	—	—	—	—	—	—	—
⅞"	0.875"	1.900	2.820	3.950	4.950	—	—	—	—	—	—	—
1⅛"	1.125"	2.160	2.820	3.950	4.950	—	—	—	—	—	—	—
1⅜"	1.375"	2.375	3.450	4.450	5.510	—	—	—	—	—	—	—
1½"	1.625"	2.720	3.450	4.950	5.510	—	—	—	—	—	—	—
2⅛"	2.125"	3.160	3.950	4.950	6.570	7.570	8.570	9.625	10.750	11.750	12.750	15.000
2⅝"	2.625"	3.660	4.460	5.510	6.570	7.570	8.570	9.625	10.750	11.750	12.750	15.000
3⅛"	3.125"	4.160	4.950	6.570	7.570	8.570	9.570	10.700	10.700	11.700	14.000	16.000
3⅝"	3.625"	4.500	5.510	6.570	7.570	8.570	9.570	10.700	11.700	12.700	14.000	16.000
4⅛"	4.125"	5.160	6.570	7.570	8.570	9.570	10.700	11.700	11.700	12.700	13.950	17.000
5⅛"	5.125"	—	7.570	8.570	9.570	10.700	11.700	12.700	12.700	13.950	14.950	18.000
6⅛"	6.125"	—	8.570	9.570	10.700	11.700	12.700	13.950	13.950	14.950	15.950	19.000

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards, with the exception of 1⅝" x 1½" cts.


COPPER TUBE ACTUAL WALL THICKNESS SINGLE LAYER DIMENSIONAL DATA*

Copper Tube Size	Copper Tube Outside Diameter	Insulation Wall Thickness										
		½"	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
⅝"	0.625"	0.495	1.075	1.390	1.915	—	—	—	—	—	—	—
⅞"	0.875"	0.485	0.945	1.510	2.010	—	—	—	—	—	—	—
1⅛"	1.125"	0.495	0.825	1.390	1.890	—	—	—	—	—	—	—
1⅜"	1.375"	0.478	1.015	1.515	2.045	—	—	—	—	—	—	—
1½"	1.625"	0.515	0.880	1.630	1.910	—	—	—	—	—	—	—
2⅛"	2.125"	0.485	0.880	1.380	2.190	2.690	3.190	3.063	4.280	4.780	5.280	6.405
2⅝"	2.625"	0.485	0.885	1.410	1.940	2.440	2.940	2.813	4.030	4.530	5.030	6.155
3⅛"	3.125"	0.485	0.880	1.690	2.190	2.690	3.190	3.100	3.755	4.255	5.405	6.405
3⅝"	3.625"	0.485	0.910	1.440	1.940	2.440	2.940	3.100	4.005	4.505	5.155	6.155
4⅛"	4.125"	0.485	1.190	1.690	2.190	2.690	3.255	3.070	3.755	4.255	4.880	6.405
5⅛"	5.125"	—	1.190	1.690	2.190	2.755	3.255	3.040	3.755	4.380	4.880	6.405
6⅛"	6.125"	—	1.170	1.670	2.235	2.735	3.235	3.165	3.860	4.360	4.860	6.385

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards, with the exception of 1⅝" x 1½" cts. *Subject to Knauf Insulation tolerances.

DIMENSIONAL DATA NESTING CHART

Copper Tube, Double Layer



COPPER TUBE DOUBLE LAYER NESTING CHART											
Copper Tube Size	Copper Tube Outside Diameter	Insulation Wall Thickness									
		1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
5/8"	0.625"	5/8 x 1/2 1½ x 1/2	5/8 x 1/2 1½ x 1	5/8 x 1 2½ x 1	5/8 x 1 2½ x 1½	5/8 x 1½ 3 x 1½	5/8 x 1½ 3 x 2	5/8 x 2 4 x 2	5/8 x 2 4 x 2½	5/8 x 2 4 x 3	5/8 x 2 4 x 4
7/8"	0.875"	7/8 x 1/2 1½ x 1/2	7/8 x 1/2 1½ x 1	7/8 x 1 2½ x 1	7/8 x 1 2½ x 1½	7/8 x 1½ 3½ x 1½	7/8 x 1½ 3½ x 2	7/8 x 2 4½ x 2	7/8 x 2 4½ x 2½	7/8 x 2 4½ x 3	7/8 x 2 4½ x 4
1¼"	1.125"	1½ x 1/2 2 x 1/2	1½ x 1/2 2 x 1	1½ x 1 2½ x 1	1½ x 1 2½ x 1½	1½ x 1½ 3½ x 1½	1½ x 1½ 3½ x 2	1½ x 2 4½ x 2	1½ x 2 4½ x 2½	1½ x 2 4½ x 3	1½ x 2 4½ x 4
1⅜"	1.375"	1⅜ x 1/2 2 x 1/2	1⅜ x 1/2 2 x 1	1⅜ x 1 3 x 1	1⅜ x 1 3 x 1½	1⅜ x 1½ 4 x 1½	1⅜ x 1½ 4 x 2	1⅜ x 2 5 x 2	1⅜ x 2 5 x 2½	1⅜ x 2 5 x 3	1⅜ x 2 5 x 4
1⅝"	1.625"	1⅝ x 1/2 2½ x 1/2	1⅝ x 1/2 2½ x 1	1⅝ x 1 3 x 1	1⅝ x 1 3 x 1½	1⅝ x 1½ 4½ x 1½	1⅝ x 1½ 4½ x 2	1⅝ x 2 5 x 2	1⅝ x 2 5 x 2½	1⅝ x 2 5 x 3	1⅝ x 2 5 x 4
2⅛"	2.125"	2⅛ x 1/2 3 x 1/2	2⅛ x 1/2 3 x 1	2⅛ x 1 3½ x 1	2⅛ x 1 3½ x 1½	2⅛ x 1½ 4½ x 1½	2⅛ x 1½ 4½ x 2	2⅛ x 2 6 x 2	2⅛ x 2 6 x 2½	2⅛ x 2 6 x 3	2⅛ x 3 8 x 3
2⅝"	2.625"	2⅝ x 1/2 3½ x 1/2	2⅝ x 1/2 3½ x 1	2⅝ x 1 4 x 1	2⅝ x 1 4 x 1½	2⅝ x 1½ 5 x 1½	2⅝ x 1½ 5 x 2	2⅝ x 2 6 x 2	2⅝ x 2 6 x 2½	2⅝ x 2 6 x 3	2⅝ x 3 8 x 3
3⅛"	3.125"	3⅛ x 1/2 4 x 1/2	3⅛ x 1/2 4 x 1	3⅛ x 1 4½ x 1	3⅛ x 1 4½ x 1½	3⅛ x 1½ 6 x 1½	3⅛ x 1½ 6 x 2	3⅛ x 1½ 6 x 2½	3⅛ x 1½ 6 x 3	3⅛ x 2½ 8 x 2½	3⅛ x 2½ 8 x 3½
3⅝"	3.625"	— —	— —	3⅝ x 1 5 x 1	3⅝ x 1 5 x 1½	3⅝ x 1½ 6 x 1½	3⅝ x 1½ 6 x 2	3⅝ x 1½ 6 x 2½	3⅝ x 1½ 6 x 3	3⅝ x 2½ 8 x 2½	3⅝ x 2½ 8 x 3½
4⅛"	4.125"	— —	— —	4⅛ x 1 6 x 1	4⅛ x 1 6 x 1½	4⅛ x 1 6 x 2	4⅛ x 2 8 x 1½	4⅛ x 2 8 x 2	4⅛ x 2 8 x 2½	4⅛ x 2 8 x 3	4⅛ x 3 10 x 3
5⅛"	5.125"	— —	— —	5⅛ x 1 7 x 1	5⅛ x 1 7 x 1½	5⅛ x 1½ 8 x 1½	5⅛ x 1½ 8 x 2	5⅛ x 1½ 8 x 2½	5⅛ x 1½ 8 x 3	5⅛ x 2½ 10 x 2½	5⅛ x 3 11 x 3
6⅛"	6.125"	— —	— —	6⅛ x 1 8 x 1	6⅛ x 1 8 x 1½	6⅛ x 1 8 x 2	6⅛ x 2 10 x 1½	6⅛ x 2 10 x 2	6⅛ x 2 10 x 2½	6⅛ x 2 10 x 3	6⅛ x 3 12 x 3

Note: All Earthwool 1000° Pipe Insulation complies with ASTM C585 Dimensional Standards.

These are suggested nesting combinations only. For other combinations choose a copper pipe size that equals the outside diameter of the insulation layer to be covered.

PROTO PVC FITTING COVER SIZING COPPER TUBE										
Copper Tube Size	Copper Tube Outside Diameter	Insulation Wall Thickness								
		½"	1"	1½"	2"	2½"	3"	3½"	4"	
5/8"	0.625"	2	7	9	11	13	15	—	—	
7/8"	0.875"	3	7	10	12	15	17	18	19	
1¼"	1.125"	4	7	10	12	15	17	18	19	
1⅜"	1.375"	5	9	11	13	15	17	18	19	
1⅝"	1.625"	6	9	11	13	15	17	18	19	
2⅛"	2.125"	8	10	12	15	17	18	19	20	
2⅝"	2.625"	9	11	13	15	17	18	19	20	
3⅛"	3.125"	10	12	15	17	18	19	20	21	
3⅝"	3.625"	11	13	15	17	18	19	20	21	
4⅛"	4.125"	12	15	17	18	19	20	21	22	
5⅛"	5.125"	—	17	18	19	20	21	22	23	
6⅛"	6.125"	—	18	19	20	21	22	23	24	

*Proto PVC Fitting Covers comply to ASTM C 585 Dimensional Standards. The above are combination sizes that fit short and long radius screwed and welded elbows, long radius welded elbows, and screwed or welded tees. Fitting sizes below heavy line will not fit 90° long radius elbows properly.

Order fitting covers for these long radius 90° sizes by specific iron pipe size and pipe insulation thickness.

PROTO PVC FITTING COVER SIZING TABLE IRON PIPE TABLE COMBINATION SHORT AND LONG RADIUS FITTING COVERS											
Iron Pipe Size	Iron Pipe Outside Diameter	Insulation Wall Thickness									
		½"	1"	1½"	2"	2½"	3"	3½"	4"	5"	6"
½"	0.840"	3	7	10	12	15	17	18	19	—	—
¾"	1.050"	4	7	10	12	15	17	18	19	—	—
1"	1.315"	5	9	11	13	15	17	18	19	—	—
1¼"	1.660"	6	9	12	13	15	17	18	19	—	—
1½"	1.900"	7	10	12	15	17	18	19	20	—	—
2"	2.375"	9	11	13	15	17	18	19	20	22	23
2½"	2.875"	10	12	15	17	18	19	20	21	22	24
3"	3.500"	11	13	15	17	18	19	20	21	23	25
3½"	4.000"	12	15	17	18	19	20	21	22	23	25
4"	4.500"	13	15	17	18	19	20	21	22	24	26
5"	5.563"	—	17	18	19	20	21	22	23	25	27
6"	6.625"	—	18	19	20	21	22	23	24	26	28
8"	8.625"	—	20	21	22	23	24	25	26	28	30
10"	10.750"	—	22	23	24	25	26	27	28	30	32
12"	12.750"	—	24	25	26	27	28	29	30	32	34
14"	14.000"	—	25	26	27	28	29	30	31	33	35
16"	16.000"	—	27	28	29	30	31	32	33	35	37
18"	18.000"	—	29	30	31	32	33	34	35	37	—
20"	20.000"	—	31	32	33	34	35	36	37	—	—
22"	22.000"	—	33	34	35	36	37	38	39	—	—
24"	24.000"	—	35	36	37	38	39	40	41	—	—

*Proto PVC Fitting Covers comply to ASTM C585 Dimensional Standards. The above are combination sizes that fit short and long radius screwed and welded elbows, long radius welded elbows, and screwed or welded tees. Fitting sizes below heavy line will not fit 90° long radius elbows properly. Order fitting covers for these long radius 90° sizes by specific iron pipe size and Earthwool 1000° Pipe Insulation thickness.

Check with your Knauf Insulation Territory Manager to ensure information is current.

The chemical and physical properties of this product represent average values determined in accordance with accepted test methods. The data is subject to normal manufacturing variations. The data is supplied as a technical service and is subject to change without notice. References to numerical flame spread ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions.

This product is covered by one or more U.S. and/or other patents. See patent www.knaufnorthamerica.com/patents

Visit knaufnorthamerica.com to learn more.

KNAUF INSULATION, INC.

One Knauf Drive
Shelbyville, IN 46176

Technical Support

(317) 398-4434 ext. 8727

info.us@knaufinsulation.com

01-20

© 2020 Knauf Insulation, Inc.