

JET STREAM® ULTRA BLOWING INSULATION COVERAGE CHART

32 LBS. BAG					
R-Value	Bags/ 1,000 Sq. Ft.	Max. Coverage/ Bag (sq. ft.)	Net Min. Weight/ Sq. Ft. (lbs.)	Thickness (in)	Density (PCF)
R-1	0.4	2,397.4	0.013	0.375	0.427
R-2	0.8	1,190.5	0.027	0.750	0.430
R-3	1.3	788.3	0.041	1.125	0.433
R-4	1.7	587.3	0.054	1.500	0.436
R-5	2.1	466.7	0.069	1.875	0.439
R-6	2.6	386.3	0.083	2.250	0.442
R-7	3.0	329.0	0.097	2.625	0.445
R-8	3.5	286.0	0.112	3.000	0.448
R-9	3.8	262.8	0.122	3.250	0.450
R-10	4.3	234.1	0.137	3.625	0.452
R-11	4.7	210.8	0.152	4.000	0.455
R-12	5.2	191.5	0.167	4.375	0.458
R-13	5.7	175.3	0.183	4.750	0.461
R-14	6.0	165.8	0.193	5.000	0.463
R-15	6.5	153.3	0.209	5.375	0.466
R-16	7.0	142.4	0.225	5.750	0.469
R-17	7.5	132.8	0.241	6.125	0.472
R-18	7.9	127.1	0.252	6.375	0.474
R-19	8.4	119.3	0.268	6.750	0.477
R-20	8.9	112.3	0.285	7.125	0.480
R-21	9.4	106.1	0.302	7.500	0.483
R-22	9.8	102.2	0.313	7.750	0.485
R-23	10.3	96.9	0.330	8.125	0.488
R-24	10.9	92.1	0.347	8.500	0.491
R-25	11.2	89.1	0.359	8.750	0.492
R-26	11.8	85.0	0.377	9.125	0.495
R-27	12.3	81.1	0.394	9.500	0.498
R-28	12.7	78.7	0.406	9.750	0.500
R-29	13.3	75.4	0.425	10.125	0.503
R-30	13.6	73.3	0.437	10.375	0.505

32 LBS. BAG

R-Value	Bags/ 1,000 Sq. Ft.	Max. Coverage/ Bag (sq. ft.)	Net Min. Weight/ Sq. Ft. (lbs.)	Thickness (in)	Density (PCF)
R-31	14.2	70.3	0.455	10.750	0.508
R-32	14.6	68.4	0.468	11.000	0.510
R-33	15.2	65.8	0.486	11.375	0.513
R-34	15.6	64.2	0.499	11.625	0.515
R-35	16.2	61.8	0.518	12.000	0.518
R-36	16.8	59.6	0.537	12.375	0.521
R-37	17.2	58.2	0.550	12.625	0.523
R-38	17.8	56.2	0.569	13.000	0.526
R-39	18.2	54.9	0.583	13.250	0.528
R-40	18.8	53.1	0.602	13.625	0.530
R-41	19.4	51.4	0.622	14.000	0.533
R-42	19.9	50.3	0.636	14.250	0.535
R-43	20.3	49.3	0.649	14.500	0.537
R-44	20.9	47.8	0.670	14.875	0.540
R-45	21.4	46.8	0.683	15.125	0.542
R-46	22.0	45.4	0.704	15.500	0.545
R-47	22.4	44.6	0.718	15.750	0.547
R-48	23.1	43.3	0.739	16.125	0.550
R-49	23.5	42.5	0.753	16.375	0.552
R-50	24.2	41.3	0.774	16.750	0.555
R-51	24.6	40.6	0.789	17.000	0.557
R-52	25.1	39.8	0.803	17.250	0.559
R-53	25.8	38.8	0.825	17.625	0.562
R-54	26.2	38.1	0.840	17.875	0.564
R-55	26.9	37.1	0.862	18.250	0.567
R-56	27.4	36.5	0.876	18.500	0.568
R-57	27.9	35.9	0.891	18.750	0.570
R-58	28.6	35.0	0.914	19.125	0.573
R-59	29.0	34.4	0.929	19.375	0.575
R-60	29.7	33.6	0.952	19.750	0.578

Knauf Insulation, Inc. | www.knaufnorthamerica.com

Tech. Support: (317) 398-4434 option 6 | info.us@knaufinsulation.com

One Knauf Drive, Shelbyville, IN 46176

© 2024 Knauf Insulation, Inc. | 04-25