

QUIET.BOX Duo and QUIET.BOX Duo Organic PEACE AND QUIET FOR TWO

**VOICE LEVEL
REDUCTION**
Classification A
according to
ISO 23351-1

BUILT-IN LED
for uniform illumination

DOOR HINGES
3D-adjustable in silver,
optional in white or black

REAR WALL
Plastic/melamine, fabric or
fixed glazing

SOLID SURFACES
choose from the K+N fabric
collection MFC (in plain and
decorative finish)
Acoustic insulation level
Rw,P 42 dB




SEAT UPHOLSTERY
choose from the K+N fabric
collection



CONTROL/ACCESSORIES
Customised equipment
as required



PROFILES
Available in a
selection of colours,
including RAL colours



**TEXTILE INSIDE
SURFACES**
for an ideal interior
acoustic choose from the
K+N fabric collection
(Economy 22, 28, 201,
202, 203, 901 and 902,
Comfort 33 and 92 or
Premium 42, 43 and 44)

ACOUSTIC GLAZING
with acoustic insulation level
Rw,P 38 dB. Door Rw,P 37 dB
(optional DIN right/DIN left)



QUIET.BOX Duo and QUIET.BOX Duo Organic INFOCARD



INTERNAL VARIANT 1
NET.WORK.PLACE bench and side table



INTERNAL VARIANT 2
Mini-office for focused working




INTERNAL VARIANT 3
QUICK.III and side table



QUIET.BOX Duo Organic
version with rounded corners

Size	2,200 x 1,200 x 2,226 mm
Required room height	2,400 mm
Ceiling	Acoustic ceiling in fabric
Wall configuration	Unrestricted design
Absorption (echo)	Yes
Voice level reduction	Classification A according to ISO 23351-1
Door	Hinged or sliding door
Ventilation	Controllable, active ventilation
Climate control	No
Lighting	Built-in and pendant lights are available
Glass modules	Large areas
Floor	Does not have its own floor, barrier-free (Optional floor available)
Installation time (excl. transport)	3 – 4 hours
Reconfiguration on the same floor	3 hours
Construction	Noisy
Flexibility	All components can be reused
Fastened to the floor of the building	No
Wire management	Electrical post in the centre of the rear wall
Sound insulation	Solid walls up to $R_{w,P}$ 43 dB, glazed sections up to $R_{w,P}$ 38 dB



1 | FABRIC CEILING
Acoustic properties

2 | CEILING TRIM PROFILE
Neat covering for ceiling structure and concealed technology

3 | OPERATING CONSOLE
Light and ventilation switches as standard version or available with touch function

4 | DOOR HINGES
3D-adjustable in silver, optional in white or black

5 | FLOOR CONNECTION
Flush-level entry, barrier-free.

