

POULTRY CHECK® MP MS – MG PROTOCOL FOR LX-200

Step 1: Protocol Setting (Read Only)

Instructions Name this protocol and select the acquisition settings. Press Next to continue.



Name:

Version :

Acquisition Settings

Bead Type: DD Gating to

Volume : microliters

Timeout : Enabled seconds

XY Heater : Enabled degrees C

Analysis Settings

Analysis Type : Min MFI Enabled Analyze results while acquiring sample

Number of standards: Use External Analysis Program

Number of controls: Analysis Program

Fit of all Standards Mean of Relicates



Step 2: Select Analytes for "Poultry Check® MP MS - MG" (Read Only)



Instructions Select analytes. Edit analyte name, units, counts, and select an intra-well normalization bead, if desired. Select an analyte on the Analysis column set the normalization bead.

Analytes

Select All

Deselect All

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

Default Analysis

Change

No Analysis

Units

Count

Apply All

Total count: Stop after bead count reaches : 100

Name	Analysis	Units	Count	Region
IgY	No Analysis	MFI	50	35
Rb anti-ch	No Analysis	MFI	50	45
Non specific control	No Analysis	MFI	50	46
MS	No Analysis	MFI	50	52
MG	No Analysis	MFI	50	54



Step 3: Plate Layout for "FM2 MS et MG" (Read Only)

Instructions Select wells to add samples and maintenance commands to the plate.



	1	2	3	4	5	6	7	8	9	10	11	12
A	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
B	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
C	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
D	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
E	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
F	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
G	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
H	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Command Sequence : Plate 1

Well	Type	ID	Dilution
------	------	----	----------

Move Command



Import List



NOTHING TO SELECT ON STEP 3