

**PACK YOUR READY-TO-USE DISHES !!**



## TECHNICAL DATA SHEETS – MINIMA WRAPPING SYSTEM

<b>Electrical supply</b>	200 / 230 V – 1 phase
<b>Power supply</b>	1 200 W
<b>Production per hour</b>	0 – 300 batch
<b>Maximum product size</b>	350 x 240 x 140 mm (L x D x H)
<b>Maximum coil diameter</b>	200 mm
<b>Maximum coil strip (width)</b>	350 mm
<b>Dimensions MINIMA opened cover</b>	930 x 550 x 580 mm (L x D x H)
<b>Dimensions MINIMA closed cover</b>	930 x 550 x 370 mm (L x D x H)
<b>Weight (Net /Gross)</b>	36 / 48 kg
<b>Programs</b>	10 positions
<b>ADVISED USE FOR PETRI DISHES</b>	2 piles of 5 Petri dishes / 1 pile of 10 Petri dishes

## TECHNICAL DATA SHEETS – WRAPPING FILM

*"This film has been carefully selected to ensure good gases exchanges to avoid Media drying and humidity issues".*

<b>Material</b>	Polyolefin – low temperature shrinking
<b>Length per roll</b>	1250 m
<b>Film width</b>	15 µm
<b>Yield</b>	14 gr /m <sup>2</sup>
<b>Heat shrink % – Method 120°C / 5mm</b>	> 50
<b>Welding resistance – Heating wire method</b>	2000 (gr /15mm)
<b>Moisture %</b>	1.9