

(510) 887-8885 | <u>info@harrenslab.com</u> 3860 BAY CENTER PLACE | HAYWARD, CA 94545

Client: LARQ, 3980 Trust Way, Hayward, CA 94545

Order Number: IN201804033 Sample Number: HR20180490108

Study: Antimicrobial efficacy of the LARQ Bottle against Escherichia coli

Method: ASTM E2315

Report Date: 5/30/2018

Certificate of Analysis

Experimental Summary:

The objective of this experiment was to test the efficacy of LARQ's UV-C LED UV technology within the application of the LARQ Bottle against water samples enriched with *E. coli*. The testing procedure was designed after discussions between LARQ and Harrens Lab and based on ASTM E2315 ("Standard Guide for Assessment of Antimicrobial Activity Using a Time-Kill Procedure") testing guidelines and was conducted at Harrens Lab Inc. in Hayward, CA.

Materials and Methods:

LARQ provided 4 stainless steel bottles and one UV-C LED cap for the testing. LARQ provided Sterile Deionized water that was used to spike the samples and treat. $E.\ coli$ (ATCC 25922) was used as the testing organism in this experiment with a starting solution of about 1.00×10^7 CFU/mL. Testing was done in 3 replicates for 2-min tests, and 6 replicates for 1-min and 3-min tests. Inoculated volumes for each run was 500 mL, out of which 50 mL was collected for LARQ internal purposes, and 450 mL was tested in a stainless bottle with UV cap (provided by LARQ) for designated run-times. Pre and post treatment aliquots were plated in serial dilutions ranging from 10^{-1} to 10^{-9} on APC Media using a pour plate technique. Plates were incubated for 48-hr at 35° C.







Results:

Table 1: Experimental results using 1-min light treatment against E. coli

Replicate	Initial Population	T-1 min	Log Reduction (T1)	% Reduction (T1)
1	1.60E+07	2.50E+03	3.81	99.9844
2	6.00E+06	6.80E+02	3.95	99.9887
3	6.00E+06	7.20E+02	3.92	99.9880
4	4.00E+06	2.12E+03	3.28	99.9470
5	5.20E+06	8.80E+02	3.77	99.9831
6	6.50E+06	1.68E+03	3.59	99.9742
Average	7.28E+06	1.43E+03	3.72	99.9775

Table 2: Experimental results using 2-min light treatment against E. coli

Replicate	Initial Population	T-2 min	Log Reduction (T2)	% Reduction (T2)
1	5.80E+06	1.00E+01	5.76	99.9998
2	2.90E+06	1.00E+01	5.46	99.9997
3	5.60E+06	1.00E+01	5.75	99.9998
Average	4.77E+06	1.00E+01	5.66	99.9998

Table 3: Experimental results using 3-min light treatment against E. coli

Replicate	initial Population	T-3 min	Log Reduction (T3)	% Reduction (T3)
1	1.10E+08	1.00E+01	7.04	99.9999
2	4.70E+06	1.00E+01	5.67	99.9998
3	7.60E+06	1.00E+01	5.88	99.9999
4	1.20E+07	1.00E+01	6.08	99.9999
5	8.40E+06	1.00E+01	5.92	99.9999
6	7.20E+06	1.00E+01	5.86	99.9999
Average	2.50E+07	1.00E+01	6.08	99.9999

Comment: No growth was detected on 3-min treated plates so a value of 10 was used to indicate the detection limit (<10 CFU).

Conclusions:

This purpose of this study was to determine how effective a LARQ Bottle was at killing *E. coli* at 1-min, 2-min, and 3-min treatments. Tables 1, 2, and 3 shows that the LARQ Bottle produced detectable log reductions of *E. coli* at 1-min, 2-min and 3-min treatments. Table 1 shows that at 1-min treatments, the LARQ Bottle yielded a log reduction of 3.72 and killed 99.9775% of *E. coli*. Table 2 shows that at 2-min treatments, the LARQ Bottle



yielded a log reduction of 5.66 and killed 99.9998% of *E. coli*. Table 3 shows that at 3-min treatments, the LARQ Bottle yielded a log reduction of 6.08 and killed 99.9999% of *E. coli*. The 3-min treatment produced the greatest log reduction and percent reduction against *E. coli*.

Respectfully Submitted,

Ming Li

General Manager

Harrens Lab Inc.

This document is intended only for the use of party to whom it is addressed and may contain information that is privileged, confidential or protected from disclosure under applicable law. Other terms and conditions may apply, visit www.harrenslab.com for more details.