

**Shower toilet, rimless, wall-hung
with lateral opening for water supply 19,5 cm,
with seat and cover
82060.1 ... 717 1**


TECHNICAL DATA

Order no.	82060.1 ... 717 1	Power supply & consumption	Rated voltage 220 to 230 V, 50/60 Hz Connection by NYM cable or H05VV-F Power consumption in use max. 1'150 W Protection rating IPX4 Protection class I
Certified to	CE, IPX4, EN 13077, SVGW Drinking water standards EN 1717	Weight	33,0 kg
matching for	commercially available installation system for shower toilets	Accessories incl.	Rotary button for shower function
Specifications	Shower toilet, rimless, wall-hung, with ceramic surface refinement LCC (only white) Washdown, flushing from 6 l to 4.5 l Concealed fixation Rotary button for shower function	Mounting acc. incl.	Inlet and outlet pipes, fastening kit M12 with connection plate, incl. mounting tool, sound insulation set (DIN 4109), water connection set 19,5 cm for shower toilet and cover for lateral opening External cable routing, order no. 89560.3
Functions	Rear shower and lady shower adjustable in pressure & position Oscillation function Temperature adjustable via mobile app (ios/Android) Self cleaning of shower head before and after every use Exchangeable shower head is fully recessed in the ceramic with a cover ring LED signal light Integrated descaling function	Mounting acc. excl.	Water connection set for shower toilet for external angle valve, order no. 89460.1 Stone screw fastening kit M12
Water pressure & temperature	Shower 7 pressure levels Flow rate ca. 3.5 l/min Temperature level via mobile app (ios/Android)	Colours	400 – White LCC, 757 – White matt
Water inlet	G 3/8" Water flow pressure range 0.1 to 1 MPa (1-10 bar) Operating temperature range +5 to +40 °C	SPECIFICATION TEXT Shower toilet, rimless, wall-hung, with lateral opening for water supply 19,5 cm, washdown Laufen CLEANET NAVIA toilet pan sanitary ceramic, with ceramic surface refinement LCC (only white) WC seat and cover Duroplast, removable, with lowering system CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717 min. 4.5/3-l-flush, dimensions 370 x 580 x 380 mm, concealed fixation Special feature: Rear shower and lady shower, with adjustable water pressure and position, temperature adjustable via mobile app (ios/Android), oscillation function, integrated self cleaning shower head before and after every use, LED signal light Order no. 82060.1 ... 717 1	
Outlet	DN 90 mm horizontal		
WC seat and cover	included Duroplast, removable, with lowering system, order no. 89160.1		

TECHNICAL DRAWINGS / S 1 : 20
