INEO INSTALLATION SYSTEM

INEOLINK
Installation element with cistern for wallhung WC and for shower toilet
H927105



TECHNICAL DATA

Order no.	H927105
Certified to	EN 14055, EN 1519
matching for	Shower toilet
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. Construction height 820 mm. With connection box for shower toilet and electronic flush plates. With support for WC ceramic with small contact surfaces. For front/top operated. Dual-Flush 6/3-l (4.5/3-l-flush), with water condensation insulation. Non-slip leg supports, rotatable foot plates, height-adjustable 0-200 mm. Capable to resist 400 kg
Water inlet	side left R 1/2, brass, matching for standard pipe systems
Outlet	DN 90/110, pipe clamp with depth adjustable
Flow pressure range	0.5-10 bar
Water temperature	max. 25°C
Tank	Installation depth: 120 mm, material PP
Installation depth	155-205 mm, wall bracket adjustable without tools
Weight	12,0 kg
Mounting acc. incl.	Angle valve 1/2”, revision box with concealed box, protection box for service opening, fastening material and 2x M12 threaded rods. Conduit pipe for feed pipe of shower toilets, WC connection set DN 90, HDPE. Drain elbow DN 90, HDPE with adapter DN 90/110, HDPE.
Mounting acc. excl.	Conduit pipe for connection of electronic flush plates, order no. VS03933 C00 000 0 Sound insulation set, order no. VS16032 C00 000 0
Accessories excl.	Flush plates INEO, dual flush with front actuation
Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation.
Otherwise	Compatible with U-profiles UW 50, UW 75, the Duofix*-System and Silent DN90*. (*are registered third party trademarks)
Colours	Surface powder coated

TECHNICAL DRAWINGS / S 1 : 20



