
CLEANET RIVA


Shower toilet, rimless, wall-hung with remote control, with seat and cover 82069.1




TECHNICAL DA	82069.1	Power supply &	Power consumption in use max. 1'400 W
Certified to matching for	CE, IPX4, EN 13077, SVGW	consumption	Power consumption in standby (boiler at ECO
	Drinking water standards EN 1717	oonsamption	or OFF, LED display OFF) < 1 W
	LIS CW2 Concealed frame with cistern for		Protection rating IPX4
	shower toilets, order no. 89466.1		Protection class I
Specifications	Shower toilet, rimless, wall-hung,	Weight	40,0 kg
	with ceramic surface refinement LCC (only white)	Accessories incl.	Touch screen remote control, with AAA batteries
	Washdown, flushing from 6 I to 4.5 I, concealed		and wall holder
	fixation		Carbon filter, splash protection
	Controller with rotary button for shower function		User manual
Functions	Rear shower and lady shower adjustable in	Mounting acc. incl.	Inlet and outlet pipes, fastening kit M12 with
	pressure, position and temperature, shower	Ü	mounting plate, sound insulation set (DIN 4109)
	duration range 15-20-25 sec		and water connection set for shower toilet
	Oscillating and pulsating cleaning mode		Mounting instruction
	4 programmable user profiles	Mounting acc. excl.	Adapter plate for Cleanet Riva Shower Toilet,
	Self cleaning of shower head before and after	•	order no. 89469.0
	every use		Stone screw fastening kit M12
	Automatic air purifier with active carbon filter	Colours	400 - White LCC, 757 - White matt
	Descaling programme	SPECIFICATION TEXT	
	Thermal cleaning heats up the entire water-	Shower toilet, rimless	, wall-hung, washdown Laufen CLEANET RIVA
	carrying system with water heated to 70°C	toilet pan sanitary ceramic, with ceramic surface refinement LCC (only	
	Light with signaling feature	white)	
Water pressure &	Shower 7 pressure levels	WC seat and cover Duroplast, removable, with lowering system	
temperature	Flow rate ca. 4.3 l/min, Power mode ca. 5.6 l/min,	CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717	
	Lady shower ca. 2.5 l/min	min. 4.5/3-I-flush, dimensions 395 x 605 x 405 mm, concealed fixation	
	Shower 7 temperature level	Special feature: Touch screen remote control, rear shower and lady	
Water inlet	concealed, G 3/8"	shower, with adjustable water pressure, temperature and nozzle position,	
	Water flow pressure range 0.1 to 1 MPa (1-10 bar)	oscillating and pulsating cleaning mode, integrated self cleaning shower	
	Operating temperature range +5 to +40 °C	head before and after every use, integrated odour filter, light with signaling	
		feature, programmable user profiles, water supply and power supply	
Outlet	DN 110 mm horizontal	leature, programmable	
Outlet WC seat and cover	DN 110 mm horizontal Duroplast, removable, with lowering system	concealed	
		·	
WC seat and cover	Duroplast, removable, with lowering system	concealed	

.....





Connection with Laufen installation system LIS CW2



Connection with commercially available installation systems

