


POLYVISION CURVED WINDOW SYSTEM

Frame your view with a curved, aerodynamic design using the Polyvision Curved semi-integrated, aluminum framed window system. The pre-mounted assembled Polyvision Curved offers a unique curved design to perfectly suit to the curved walls of your van.



ENJOY THE VIEW WITH A CURVE

Curved, flush design



Curved, aerodynamic, flush design, only suitable for curved walls

Additional Features

- Manually operated tilt window
- Vehicle installation location: side and rear
- Double pane, cast acrylic window with a thermoformed bulged inward inner sheet and curved thermoformed flush outer sheet
- Designed for curved walls with radius 4991 mm
- Unique integrated thermal bridge inside

Setting up your Polyvision Curved

Contact our sales department to customize your complete window system, including sizes, standard parts, system options and accessories.

Step 1: The basics

We will need to know wall aperture and thickness. The table below provides a range of available options.

Step 2: Standard parts

The sales representative will walk you through the customization of standard parts required for installation and operation, including catches, stays, mounting clamps, screws and more.

Mounting clamps in specific size				
Standard	Other Options			
Automatic stays with screwed installation	Manual tubular stays with screwed installation			
Screwed catches without lock button	Screwed catches with lock button			



Screwed catches

Includes integrated screwed catches with or without lock button

Aluminum framed system



Strong and lightweight powder-coated aluminum frame

window frame to reduce condensation

- Pre-assembled for quick and easy installation
- Opens in any position due to the tubular or automatic stays
- Locking plates feature a special position for extra ventilation while sleeping or away from the vehicle
- Entire system is maintenance-free and easy to clean

Step 3: System options

Customize the design with the options below.

	Standard	Other Options			
Window color (outer sheet)	Grey	Grey	Privacy black	Privacy black	
Window color (inner sheet)	Transparent	Opal	Transparent	Opal	
Screen print color	Black	Silver metallic	Graphite	No screen	
Frame color	Black	Silver metallic	Graphite	Traffic white	

Step 4: Accessory options

Complete the system with add-on accessories.

- Interior blind and flyscreen
- Cover profile

Step 5: Contact us

↔ Standard Wall Aperture Ranges		Well As estimated District Har Ha	Duild the their bet		
₩н	14. W	Wall Aperture Radius	Build-Up Height From Wall	Wall Thickness	Product Weight
300 mm to 600 mm	220 mm to 1.300 mm	75 mm	7 mm to 17 mm	24 mm to 44 mm	1,4 kg to 9,8 kg

All window systems should be installed by professionals

