

Vehicle Observation System



Side Camera with LED Marker Light



Vision S Monitor
(available in 4.3", 5" and 7")



Doorway/Rear Camera



Rear Camera with LED Marker Light



Interior Table Stand



Windshield Mount
















































7-Way Adapter*

- View up to four cameras at the same time (5" and 7" only)
- Wireless camera transmission up to 492 ft.
- 2.4Ghz digitally locked connection
- Night vision for low light situations
- Motion-detect cameras for added security
- 5" and 7" anti-glare touch screen monitors
- Easy installation with patented bracket design
- Waterproof (IP65)
- Microphone and Audio
- Vibrationsmart™ designed and engineered for vibration resistance
- Climatesmart™ designed and engineered for extreme temperatures

* Sold separately (part no. F2BC002XXBK)

Bundles

FOS43TASF	4.3" Monitor + Doorway Security/Rear Camera + Windshield Mount	 +  + 
FOS05TASF	5" Monitor + Doorway Security/Rear Camera + Windshield Mount + Interior Table Stand	 +  +  + 
FOS05TASM	5" Monitor + Rear Camera with LED Marker Light + Windshield Mount + Interior Table Stand	 +  +  + 
FOS05TAEM	5" Monitor + Rear Camera with LED Marker Light + Side Camera with LED Marker Light (left & right) + Windshield Mount + Interior Table Stand	 +  +  +  + 
FOS05TAEN	5" Monitor + Side Camera with LED Marker Light (left & right) Doorway Security/Rear Camera + Windshield Mount + Interior Table Stand	 +  +  +  + 
FOS07TASF	7" Monitor + Doorway Security/Rear Camera + Windshield Mount + Interior Table Stand	 +  +  + 
FOS07TASM	7" Monitor + Rear Camera with LED Marker Light + Windshield Mount + Interior Table Stand	 +  +  + 
FOS07TAEM	7" Monitor + Rear Camera with LED Marker Light + Side Camera with LED Marker Light (left & right) + Windshield Mount + Interior Table Stand	 +  +  +  + 
FOS07TAEN	7" Monitor + Side Camera with LED Marker Light (left & right) Doorway Security/Rear Camera + Windshield Mount + Interior Table Stand	 +  +  +  + 
FOS07TAPM	7" Monitor + Rear Camera with LED Marker Light + Side Camera with LED Marker Light (left & right) + Doorway Security/Rear Camera + Windshield Mount + Interior Table Stand	 +  +  +  +  + 

Cameras

FCE48TASH	Side Camera with LED Marker Light (left & right)	
FCN48TASF	Doorway Security/Rear Camera	

Specifications

Camera & Monitor		Camera	Rear with LED Marker Light	Side	Doorway/Rear	Monitor	
Supply Voltage	DC8 to 30V	Image Distance	Up to 16 ft.	Up to 39 ft.	Up to 16 ft.	LCD Power Off	<30mA@12V
Wireless Frequency	2.4GHz	CMOS Size	1/3"	1/3"	1/3"	LCD Backlight On	<500mA@12V
Wireless Range	Up to 492 ft.	Optical Lens	F2.0	F2.5	F2.0	LCD Backlight Off	<300mA@12V
Transmitting Speed	6 Mbps	IR Cut Filter	850nm automatic	850nm automatic	850nm automatic	LCD Size	7"/5"/4.3"
Receiving Sensitivity	-88 +/-3dBm	View Angle	120°	65°	120°	LCD Resolution at 1view	720 x 480 (4.3": 480 x 272)
Decompression Form	H.264	Current (IR On)	<400mA@12V	<500mA@12V	<400mA@12V	LCD Brightness	4.3": 240cd/m ² 5": 420cd/m ² 7": 170cd/m ²
Delaying Time	< 250ms	Current (IR Off)	<250mA@12V	<250mA@12V	<250mA@12V	LCD Contrast	4.3": 900:1 5": 600 : 1 7": 300 : 1
		Camera Pixel	720 x 480	720 x 480	720 x 480	LCD Viewing Angle	4.3": L/R75, U60, D70 5": L/R65, U50, D60 7": L/R80, U60, D70
		Waterproof	IP65	IP65	IP65	LCD Aspect Ratio	16:9

