

PRIMO WINDOW SYSTEM

Start enjoying the view with the Primo non-integrated, hinged window system. The Primo offers an outstanding view wether you're on the road or at the campsite.





Design features

POLYPLASTIC



Primo windows systems feature a bulged, robust design with solid edges

Rust-resistant



Screw or glue connected aluminum hinge bar is available in three powder-coated colors

Standard part selection



Standard parts can be customized based on the unique configuration of the window system

Additional Features

- Top-hung installation on the outside of a wall aperture
- Installation on straight walls
- Double pane, cast acrylic window with a flat unformed inner sheet and thermoformed outer sheet
- Easy-to-use, aluminum tubular or automatic stays allow for opening in every position, with or without catch
- Entire system is maintenance-free and easy to clean
- Integrated Polyfix catches to easily open and close the window with an optional lock button to increase vehicle security
- Durable, waterproof rubber profile guarantees a watertight seal between the wall and window system
- Locking plates feature a special position for extra ventilation while sleeping or away from the vehicle

Setting up your Primo

Contact our sales department to customize your complete window system, including sizes, standard parts, system options and accessories.

Step 1: The basics

We will need to know wall aperture and thickness. The table below provides a range of available options.

Step 2: Standard parts

The sales representative will walk you through the customization of standard parts required for installation and operation, including catches, stays, rubber seal, insert band, locking plates, hinge bar and more.

Standard	Other Options
Automatic stays with Polyfix installation	Tubular stays with Polyfix installation
Catches without lock button	Catches with lock button

Step 3: System options

Customize the design wiht the options below.

	Standard	Other Options			
Window color (outer sheet)	Grey	Grey	Privacy black	Privacy black	
Window color (inner sheet)	Transparent	Opal	Transparent	Opal	
Screen color	Black	Silver metallic	Graphite	No screen	
Hinge bar color	Black	Silver metallic	Graphite		

Step 4: Accessory options

Complete the system with add-on accessories.

• Interior blind and flyscreen

Step 5: Purchase

Approve the quotation and place a order.

*··· Standard Wall Aperture Ranges			Ton Oornor	Dubber Cool Mall	Duild Un Hainba	Dueduet
₩Н	12. W	Wall Aperture Radius	Top Corner Radius	Rubber Seal Wall Thickness Range		Product Weight
250 - 800 mm	350 - 1.450 mm	75 mm	16 mm	20 to 40mm	27 - 37 mm	1,3 - 6,4 kg

All window systems should be installed by professionals. For additional technical specifications, please contact your sales representative.