

9,000 BTU/H ONE-WAY CASSETTE INDOOR

SUBMITTAL COVER SHEET

PROJECT NAME		
ARCHITECT		
ENCINEED		
CONTRACTOR		
REFERENCE		
SUBMITTED BY	DATE	

Indoor Unit (IDU):	Wireless Remote	
DRAL09F1A	Control	

		,
SPECIFICATIONS		
Cooling Capacity (BTU/hr)		00
Heating Capacity (BTU/hr)	11000	
Voltage/Phase/Frequency	208-230V, 1 Phase, 60 Hz	
Voltage Range	187-253V	
	Low	235
Indoor Unit Air Flow (CFM)	Medium	259
	High	294
Drain Port O.D.	1"	
Drain Port Lift	20.8	
Recommended Breaker (Amps)	15	
	Low	33

Medium

38

R410A

High

PRODUCT FEATURES

- Single or multi-zone compatible
- Wireless Remote Control with "Follow Me" Technology
- Slim design for easy install between 16" joists
- Serviceable from below
- Washable filter
- · Humidity sensor
- Built in drain pump
- Sleep Mode
- Turbo Mode
- 24-Hour Timer Feature
- Quiet operation as low as 31 dB
- High efficiency up to 24 SEER2

LINE SET REQUIREMENTS		
Connection Type	Flare	
Liquid	Ø1/4" (Ø6.35mm)	
Gas	Ø3/8" (Ø9.52mm)	

DIMENSIONS AND WEIGHT		
Unit Dimensions	Width	50-5/16"
	Depth	13-3/16"
	Height	9"
Carton Dimensions	Width	57-5/8"
	Depth	22-1/2"
	Height	22-1/2"
Net Weight	58.4 lbs.	
Gross Weight	81.3 lbs.	





Sound Pressure (dB(A))

Refrigerant



9,000 BTU/H ONE-WAY CASSETTE INDOOR

IDU DIMENSIONS - DRAL09F1A







