legrand®

ON-Q

Mini Grommets

Model
HT3401S-WH-2PK
HT3401-WH-4PK

OWNERS GUIDE

Doc. #1507352 08/23 Rev B



IMPORTANT SAFETY INSTRUCTIONS

PLEASE READ ENTIRE MANUAL PRIOR TO USE – SAVE THESE INSTRUCTIONS

⚠ **CAUTION:** Avoid potential personal injuries and property damage!

- **For low voltage cabling only (HDMI, audio, coax or data cabling), DO NOT run power cords in-wall.**
- Please read through these instructions completely to be sure you're comfortable with this easy install process.
- Do not use this product for any purpose not explicitly specified by manufacturer.
- Manufacturer is not responsible for damage or injury caused by incorrect assembly or use.
- If you do not understand these instructions or have doubts about the safety of the installation, assembly or use of this product, contact customer service.

Parts Included

⚠ **WARNING:** This product contains small items that could be a choking hazard if swallowed.

Before starting assembly, verify all parts are included and undamaged. If any parts are missing or damaged, do not return the damaged item to your dealer; contact Customer Service. Never use damaged parts!



Grommet

Model HT3401S-WH-2PK	Model HT3401-WH-4PK
Qty. 2	Qty. 4

Model
HT3401S-WH-2PK



Driver Bit
(hole saw)



Hole Saw
2 in.

Tools Required

Tape Measure



Pencil

Electric Drill



Phillips Screwdriver

Model
HT3401-WH-4PK

2 inch Hole Saw



STEP 1 ! Verify Wall Compatibility



This Cable Kit is designed to fit into both interior and exterior walls constructed with:

! Minimum Space into Wall: 1 ½ in.

! Minimum Drywall Thickness: 1/2 in.



NOTE: Walls with blown-in type insulation may require removal of some insulation inside the cavity.

STEP 2 Drill Holes

a Assemble Hole Saw







b Drill Holes

Drill the holes at your desired locations.

! **BEFORE drilling, Verify your cable length.**



Hole Diameter:
2.00 in. (50.8mm) MIN
2.13 in. (54.0mm) MAX

STEP 3 Assemble [one (1) grommet illustrated]

a Insert Keystone Connector



b Route and Connect Cable



TIP: Use a fish tape to pull cables through the wall.

c Insert Grommet





d Lock Grommet



! **DO NOT remove the screws**

e Connect Cable



TO REMOVE



Legrand and its affiliated corporations and subsidiaries (collectively, "Legrand"), intend to make this manual accurate and complete. However, Legrand makes no claim that the information contained herein covers all details, conditions, or variations. Nor does it provide for every possible contingency in connection with the installation or use of this product. The information contained in this document is subject to change without notice or obligation of any kind. Legrand makes no representation of warranty, expressed or implied, regarding the information contained herein. Legrand assumes no responsibility for accuracy, completeness or sufficiency of the information contained in this document.

©2023 Legrand. All rights reserved.

legrand®
60 Woodlawn Street
West Hartford, CT 06110
1-877-BY-LEGRAND