

PARALLAX THIN

Da-Lite's Parallax® Thin screen has been re-engineered to offer a convenient alternative to rigid screens that ship assembled in large crates. This innovative solution offers wider sizes with a smaller shipping footprint, enhancing logistics and cost-efficiency. Specifically designed for ultrashort throw projectors, this 1/2" thin bezel fixed frame screen features the new Ambient Light Rejection (ALR) screen surface - Parallax® Pure UST 0.6. Available in 16:9 HDTV and 21:9 Ultrawide formats it complements our extensive 21:9 offering, ideal for larger spaces with Microsoft Teams Front Row setups or collaboration spaces where ambient light control is essential.

Delving deeper into the screen surface, each layer of Parallax Pure plays a crucial role in preserving image quality in high ambient light environments. The ambient light-rejecting technology incorporates a micro-layered optical lens system that rejects light. Some layers absorb light, while a special saw-toothed-shaped layer blocks light from above, preserving high-contrast, bright images even in brightly lit environments. This technology mimics the look of a television but without the glare from windows or lighting fixtures.

Features

- Parallax Pure UST 0.6 surface for ultra short-throw projectors (0.4:1 throw or less)
- Thin 1/2" bezel aluminum frame wrapped in Pro-Trim® fabric
- 1.625" depth
- Ships disassembled via Parcel for lower shipping costs and easy maneuverability in the space



HDTV (16:9) Format Dimensions

Viewing Area (H x W)		Overall Dimensions	
In.	Cm	In.	Cm
49" X 87"	124 X 221	50" X 88"	127 X 224
54" X 96"	137 X 244	55" X 97"	140 X 246
59" X 104.5"	150 X 265	60" X 105.5"	152 X 268

Ultrawide (21:9) Format Dimensions

Viewing Area (H x W)		Overall Dimensions	
In.	Cm	In.	Cm
40.5" X 96"	103 X 244	41.5" X 97"	105 X 246
50.5" X 120"	128 X 305	51.5" X 121"	131 X 307
59" X 140"	150 X 356	60" X 141"	152 X 358

Available with the Following Screen Surfaces



Parallax Pure UST 0.6

Horizontal Half Angle: 80°

Vertical Half Angle: 55°

Gain: 0.6

Parallax Pure UST 0.6 Projector Placement

The Ultra Short Throw projector must be mounted below the screen for the projected light to be reflected by the screen surface.

LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

FOR YOUR IMAGE | [legrandav.com](https://www.legrandav.com)

USA 866.977.3901 av.da-lite.support@legrand.com CANADA 877.345.4329 av.da-lite.support@legrand.com

EMEA +31 495 580 840 av.emea.sales@legrand.com APAC +852 2145 4099 av.asia.sales@legrand.com

©2024 Legrand AV Inc. 240914 Rev A 12/24 Da-Lite is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.