

Reg. EC/1907/2006 - Reg. (EU) n.830/2015-29 CFR 1910.1200 (OSHA-HCS)

Issue: 08/10/2014



Version 1.2

Revision: 25/01/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier: CC PHS289 **PERFETTO ULTRA CLEAR COAT**
- 1.2. Relevant identified uses of the substance or mixture and uses advised against: CLEAR COAT FOR CAR BODY
- 1.3. Details of the supplier of the safety data sheet: LEVEL Finish LLC 1161N 1210W STE 200 St. George, UT 84770 USA.
For further information concerning the use of this safety data sheet please phone 1(844) 340-5677
Chemical technician in charge of the safety data sheet: r.basetti@allchem.it
- 1.4. Emergency telephone number: Chemtrec 1(800) 424-9300

SECTION 2: Hazard identification

- 2.1.1 In compliance with Reg. EC n. 1272/2008 the mixture is classified:  GHS02  GHS07 - Flam. Liq 3 H226 - Skin Sens. 1 H317 - STOT SE 3 H336 - Aquatic Chronic 3 H412 - EUH066.
- 2.1.2. Classification according to 29 CFR 1910.1200 (OSHA-HCS): Flammable liquids catg. 3, Skin Sensitizer catg. 1, Specific target organ toxicity (single exposure) catg. 3 (narcotic effects),
- 2.2. GHS Label elements according to OSHA-HCS:



Hazard pictograms:

Signal word: **Warning**

Hazard Statements: H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction
H336 May cause drowsiness or dizziness.

Precautionary Statements











- Prevention: P210 Keep away from heat / sparks / open flames / hot surfaces. – No smoking.
P233 Keep container tightly closed.
P240 Ground / bond container and receiving equipment.
P242 Use only non sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P280 Wear protective gloves / eye protection / face protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
P271 Use only outdoors or in a well-ventilated area.
- Response: P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use dry chemical (BC) or Carbon dioxide (CO₂) for extinction.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P304+P340 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- Storage: P235 Keep cool.
P403 Store in a well-ventilated place.
- Disposal: P273 Avoid release to the environment.
P501 Dispose of contents / container in accordance with local, state and federal regulations.





Supplementary label elements:

2. Repeated exposure may cause skin dryness or cracking. Harmful to aquatic life with long lasting effects. Ready-to-use product contains 418 g/L COV (Dir. 2004/42/CE, IIB, cat., d, max. 420 g/L).
 3. Other hazards
- None of the components of the mixture satisfy the criteria for the identification of PBT and vPvB.

SECTION 3: Composition / information on ingredients

3.2. Mixtures: Dangerous components (classification according to Reg. (EC) n. 1272/2008 and 29 CFR 1910.1200 OSHA-HCS)

| Denomination | CAS N° | Conc. % in weight | classification according to Reg. (EC) n. 1272/2008 | | | N o t e |
|---|---|----------------------|--|---|--------------------------------------|------------------|
| | ECHA reg. N° | | Hazard class and category | Pictograms and labeling codes | Hazard State ment Code | |
| | EC N° | | | | | |
| n-butyl acetate | 123-86-4 01-2119485493-29 204-658-1 | 40 ÷ 45 % | Flam. Liq. 3 STOT SE 3 |   Wng | H226 H336 EUH066 | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 01-2119475791-29 203-603-9 | 5 ÷ 10 % | Flam. Liq. 3 |  Wng | H226 | |
| propylene carbonate | 108-32-7 01-2119537232-48 203-572-1 | 1 ÷ 5 % | Eye Irrit. 2 |  Wng | H319 | |
| heptan-2-one | 110-43-0 01-2119902391-49 203-767-1 | 1 ÷ 5 % | Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 STOT SE 3 |   Wng | H226 H302 H332 H336 | |
| solvent naphtha (petroleum), light arom. | 64742-95-6 01-2119486773-24 265-199-0 | 1 ÷ 5 % | Flam. Liq. 3 Asp. Tox. 1 Skin Irrit. 2 STOT SE 3 Aquatic Chronic 2 |     Dgr | H226 H304 H315 H336 H411 | P |

| | | | | | |
|---|--------------------------|---------|--|---|----------------------|
| Reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxy poly(oxyethylene) | 01-0000015075-76 | < 0,8 % | Skin Sens. 1 Aquatic Chronic 2 |   Wng | H317 H411 |
| Mixture of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 41556-26-7 82919-37-7 | < 0,5 % | Skin Sens. 1 Aquatic Acute 1 Aquatic Chronic 2 |   Wng | H317 H400 H411 |

Note P: the substance is not classified as cancerogenic and mutagenic because it contains less than 0,1% of benzene in weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

- **Inhalation.** Remove the patient to a well aired place, keep him warm and make him rest. If respiration is irregular or has stopped, give him artificial respiration. In case of loss of consciousness, keep him in a restful position and consult a doctor.
- **Skin contact.** Immediately remove contaminated garments. Wash the parts involved very thoroughly with soap and water or with an appropriate detergent. Do not use solvents or thinners.
- **Eye contact.** Rinse with plenty of fresh water for at least 15 minutes keeping the eyelids wide open. Remove contact lenses, if present and easy to do. If necessary, call a specialist.
- **Swallowing.** In case of accidental swallowing, consult a doctor immediately. Make the patient rest. Do not induce vomit.

4.2. Most important symptoms and effects, both acute and delayed: No further information available.

4.3. Indication of any immediate medical attention and special treatment needed: No further relevant indication.

SECTION 5: Firefighting measures

5.1. Extinguishing media: Extinguish with carbon dioxide, powders, foam, sprayed water. Do not use water jets.

5.2. Special hazards arising from the substance or mixture: combustion can develop toxic fumes containing carbon monoxide and nitrogen oxides.

5.3. Advice for firefighters: Cool with sprayed water any closed containers exposed to the fire. Do not breath fumes developed from the fire or wear breathing apparatus. Prevent extinguishing liquids from entering sewer systems or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures: Do not breathe in vapours, use the personal protective equipment for person/eyes and respiratory tract. Keep away any source of ignition and ventilate the area. Vapours are heavier than air and may form flammable mixtures along the ground: provide adequate ventilation.

6.2. Environmental precautions: Prevent spills from entering manholes and drains.

6.3. Methods and material for containment and cleaning up: In case of accidental spillage, check and absorb any spilled product with sand and inert materials. Put the contaminated material into tight containers and dispose of as waste according to laws in force. Use no-sparking tools. If the material is to be recovered by aid of aspirators, keep away possible sources of ignition. Do not throw waste material into the sewer system. Clean the area involved with water or detergent liquid. Do not use any solvents.

6.4. Reference to other sections: see also sections 8 and 13.

SECTION 7: Handling and Storage

7.1. Precaution for safe handling: Ensure an adequate ventilation and/or localised suction systems in work places.

The material can accumulate electrostatic charges which may cause sparks (source of ignition). Use appropriate storage procedures and grounding systems. Use only in well-ventilated places.

For personal protection devices as see paragraph 8. Do not smoke, eat or drink in working areas.

7.2. Condition for safe storage, including any incompatibilities. Store between 15 and 25°C in a dry and well aired place. Keep containers well closed and away from heat sources, sparks and open flames. Do not smoke. Do not allow access to the storage area to unauthorized persons. Keep away from oxidative agents, peroxides, strong acids. Open the containers slowly to control possible pressure losses. Store in a cool and well-ventilated place. Always use packaging of the same type as the original ones. Definitive storage package, package for decanting and related equipment must be grounded to prevent accumulation of electrostatic charges.

Reg. EC/1907/2006 - Reg. (EU) n.830/2015-29 CFR 1910.1200 (OSHA-HCS)

Issue: 08/10/2014

Version 1.2

Revision: 25/01/2016

Compatible packaging materials and coatings (chemical compatibility): carbon steel; stainless steel; polyethylene; polypropylene; polyester; PTFE.
Not compatible materials and coatings: natural rubber; butyl rubber; polystyrene.

7.3. Specific end use(s): No further relevant indication.

SECTION 8: Exposure control / Personal protection

8.1. Control parameters

| Professional Exposure Limits: Component | ACGIH 2014 | | | | DIR 2000/39/CE | | | | Note |
|--|---------------|-------------------|----------|-------------------|----------------|-------------------|-----|-------------------|------|
| | TLV - TWA (1) | | STEL (2) | | Note | TLV - TWA (1) | | STEL (2) | |
| | ppm | mg/m ³ | ppm | mg/m ³ | ppm | mg/m ³ | ppm | mg/m ³ | |
| n-Butyl acetate 123-86-4 | 150 | 713 | 200 | 950 | | | | | |
| heptan-2-one | 50 | 233 | | | 50 | 238 | 100 | 475 | skin |
| 2-methoxy-1-methylethyl acetate | | | | | 50 | 275 | 100 | 550 | skin |

1) Limit for long exposure 2) Limit for short exposure 3) Substance with indicator of Biological Exposure

8.2. Exposure controls

Protection of respiratory tract. The workplaces have to be adequately ventilated. Workplaces have to be equipped with localised suction systems. In working places with insufficient ventilation, it is essential to use protection systems for the respiratory tract, such as masks with filter of the type A according to UNI EN 141 regulations.

Adopt explosion-proof ventilation systems.

Hands protection. Wear PVF or nitrile rubber gloves for brief contact (recommendation: at least protective index 2, corresponding to > 30 min. permeation according to EN374).

Eyes protection. Safety glasses with side shields (frame goggles for example. EN 166).

HYGENIC MEASURES: Do not breathe vapours – Avoid contact with skin and eyes – Keep away from food and drinks – Before breaks and at the end of work wash hands. Remove contaminated garments and wash them before use them again. Persons with an inclination to skin affections and other signs of skin hypersensitivity must avoid any contact with the product. Use anti-static working clothes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Appearance: | colourless transparent liquid |
| Odour: | characteristic of solvents |
| Olfactory threshold: | data not available for the mixture |
| pH: | n.a. |
| Melting point: | data not available for the mixture |
| Flash point: | 29°C (UNI EN ISO 3680:2005) |
| Evaporation rate: | data not available for the mixture |
| Flammability limits (Butyl acetate): | 1,7÷7,6 % in volume |
| Vapour pressure: | data not available for the mixture |
| Boiling range: | data not available for the mixture |
| Decomposition temperature: | data not available for the mixture |
| Vapour density (Butyl acetate): | 4,83 Kg/m ³ at 20 °C |
| Density (at 20°C): | 1,006 Kg/L |
| Solubility in water (Butyl acetate): | 7 g/L |
| Distribution coefficient: n-octanol / water: | data not available for the mixture |
| Self-ignition temperature: | data not available for the mixture |
| Viscosity (at 40°C): | > 500 mm ² /s |
| Explosive properties: | n.a. |
| Oxidising properties: | see danger identification section |

9.2. Other information: No further relevant indication.

SECTION 10: Stability and reactivity

10.1. Reactivity: no data available

10.2. Chemical stability: The product is stable under the recommended conditions of storage and use (see paragraph 7).

10.3. Possibility of hazardous reactions: If exposed to high temperatures may form explosive mixtures vapour/air.

10.4. Conditions to avoid: heat, flames and sparks.

10.5. Incompatible materials: strong alkalis and strong acids, oxidizing agents, isocyanates, anhydrides.

10.6. Hazardous decomposition products: none under normal condition of use; If exposed to high temperatures, it can give rise to hazardous decomposition products, such as carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects:

| | | |
|--|-------------------------------|----------------|
| Acute toxicity of Butyl acetate 123-86-4: | LD ₅₀ oral rat | 10800 mg/Kg |
| | LC ₅₀ inhaling rat | 9.5 mg/L/4h |
| Acute toxicity of heptan-2-one: | LD ₅₀ oral rat | 1600 mg/Kg |
| | LC ₅₀ inhaling rat | > 16.7 mg/L/4h |
| Acute toxicity of 2-methoxy-1-methylethyl acetate: | LD ₅₀ oral rat | 7900 mg/Kg |
| | LC ₅₀ inhaling rat | 55.2 mg/L/4h |

11.2 Chronic effects: concentrations of vapours exceeding recommended exposure levels are irritating to eyes and respiratory tract, can cause headaches and dizziness, have an anaesthetic effect and cause other effects on the central nervous system. Repeated and/or prolonged skin contact with low viscosity materials may degrease the skin with possible development of skin irritation and dermatitis.

11.3. Irritation: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

11.4. Sensitization of the respiratory tract: inhalation of high concentrations may cause symptoms like headache, dizziness, fatigue, nausea and vomiting.

11.5. Mutagenicity on germ cell, mutagenicity assessment: the product has not been tested. Toxicological data were derived from the properties of individual components.

SECTION 12: Ecological information

12.1 Toxicity: no specific data is available on the preparation.

12.2 Persistence and degradability: no specific data is available on the preparation; mixture components are partially biodegradable and compatible with biological treatment in waste treatment plants.

12.3. Bioaccumulative potential: components of the mixture have a low bioaccumulative potential.

12.4. Mobility in soil: no specific data available on the preparation.

12.5. Results of PBT and vPvB assessment: The mixture does not contain substances considered PBT or vPvB.

12.6 Other adverse effects: data not available.

SECTION 13: Disposal considerations

13.1. Waste treatments methods: Do not discharge the product or residues of treatment into sewer systems or water courses. Waste has to be disposed of in compliance with D. Lgs. Regulations of 3 April 2006, n. 152 (European Directives 91/156/EEC, 91/689/EEC and 94/62/EC). Waste may be treated in waste water depuration plants or in incineration plants. Contaminated containers: Empty containers should be taken for recycling, recovery or disposal as waste.

SECTION 14: Transport information

14.1. UN number: UN 1263

14.2. UN proper shipping name: PAINT

14.3. Transport hazard class(es): Class 3, hazard label N. 3

14.4. Packing group: III

14.5. Environmental hazards: The substance is not classified either as dangerous for the environment or as marine pollutant. EMS F-E, S-E.

14.6. Special precaution for users: see SECTION 7.

14.7. Transport in bulk according to Annex II or MARPOL 73/78 and the IBC Code: not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

The components of the mixture are included in Annex I of Dir. 96/82/EC (Seveso).

The preparation itself falls within the scope of Directives 1999/13/EC and 2004/42/EC (Annex II, B) on limits for the emissions of volatile organic compounds (VOC) in vehicles refinishing products.

15.2. Chemical safety assessment: no assessment on chemical safety has been carried out for the mixture.

SECTION 16: Other information

Revision for adaptation to EU Regulation n. 605/2014, modified sec. 2, sec. 3, sec.9.

The mixture is classified in compliance with Reg. (EC) 1272/2008 and 29 CFR 1910.1200 OSHA-HCS:

H 226 Flam. Liq. 3: Flammable liquid of category 3, official laboratory method.

H 317 Skin Sens. 1: Skin sensitization of category 1A, conventional calculation method.

H 336 STOT SE 3: Specific target organs toxicity single exposure of category 3, conventional calculation method.

H412 Aquatic Chronic 3: Harmful to aquatic life of category 3, conventional calculation method.

Full text of the hazard statements not indicated at sections 2 and 3:

| | |
|-------|--|
| H 302 | Harmful if swallowed. |
| H 304 | May be fatal if swallowed and enters airways. |
| H 315 | Causes skin irritation |
| H 319 | Causes serious eye irritation. |
| H 332 | Harmful if inhaled. |
| H 400 | Very toxic to aquatic life. |
| H 411 | Toxic to aquatic life with long lasting effects. |

Legislation of reference in Italy:

D.M. 28/4/97 – D.M. 28/02/2006 - Classification and labelling of dangerous substances.

D. Lgs. 14/03/2003 – D.Lgs. 28/07/2004 Classification, packing and labelling of dangerous preparations.

D.M. 7/9/2002 - Safety Data Sheets.

D.P.R. 547/55 - D.P.R. 303/56 - D. Lgs. 81/08 - Industrial prevention, security and hygiene.

D.Lgs. 152/2006 – Environmental code.

Legend: TLV-TWA (Threshold Limit Value-Time Weighted Average), TLV-STEL (Threshold Limit Value-Short Term Exposure Limit).

The data contained in this safety sheet are based on our current knowledge and are supplied in compliance with Reg. (EU) n. 830/2015 and 29CFR 1910.1200 OSHA-HCS. The product must not be used for purposes which are different from those indicated under point 1 prior to having obtained specific written instructions. No responsibility is taken for any improper use. It is always the user's liability to conform to the regulations of hygiene, safety and environmental protection foreseen by laws in force. The information contained in this safety data sheet is to be understood as a description of the product for safety purposes, it is not to be considered as a guarantee of its properties.