

Optional Accessories



Wall Mounts

Articulating Mounts provide smooth tilt, swivel and articulating action from 9° to 11-7/8° from the wall, and are available for all SunBriteTV models.

Tilt Mounts provide smooth tilt and are available for 32" and 46" models

Ceiling Mount (not shown)

Provides tilt. Includes adjustable extension column and ceiling plate. Available for all models.

SunbriteTV mounts include stainless steel hardware, and meet VESA standards.

Deck/Planter Pole

The pole and supporting flange are made from heavy-gauge aluminum or zinc-plated galvanized steel, and are powder-coated to eliminate corrosion issues. The pole can be set in concrete, in a planter or bolted directly to a flat surface, such as a patio or pool deck.

Note: Mounting bracket is not included.

Requires purchase of wall mount.

46" Deck/Planter Pole dimensions:

3"W x 3"D x 62"H Mounting Flange is 12"W x 12"D

23" and 32" Deck/Planter Pole dimensions:

3"W x 3"D x 62"H Mounting Flange is 8"W x 8"D



Outdoor Dust Cover

This fitted outdoor dustcover is constructed with weatherproof 4-ply polypropylene UV protection fabric and velcro straps for a secure fit.

Outdoor Dust Covers are available for all models.

SunBriteTV RadioFM™

RadioFM is a wireless transmitter that sends audio from the SunBriteTV to your FM radio stereo system. RadioFM allows SunBriteTV's audio to be played through your spa's built-in speakers or any portable FM radio.

RadioFM is available for all models..



Water-Resistant Remote Control

Units come equipped with a water-resistant remote control that run on long-life lithium batteries.

The water-resistant remote control is an *included accessory* with all models.

For complete descriptions, dimensions, and part numbers of SunbriteTV accessories, please visit the Product Page at www.sunbriteTV.com.

SunBriteTV LCD TVs are Designed for Outdoor Installation

- ☉ SunBriteTV LCD screens are significantly brighter than standard indoor LCD TVs
- ☉ All-weather enclosure protects internal components from rain, dirt, insects and scratches
- ☉ A contrast-enhancing, anti-reflective and scratch-resistant window protects the LCD screen
- ☉ Baffled and filtered, airflow system keeps unit cool and dry in temperatures up to 122°F.
- ☉ Internal thermostatically-controlled heater protects TV in temperatures as low as -24° F.
- ☉ Innovative water-tight cable entry system with pass-through design keeps cables dry and allows for easy hook-up
- ☉ Watertight, user-friendly operator controls
- ☉ Water-resistant remote control
- ☉ Optional wall and ceiling mounts and deck/planter poles are weatherized and include stainless steel hardware

SunBriteTV®



All-Weather Outdoor LCD TV



 **SunBriteTV**
www.sunbriteTV.com

LCD Screen: 46" diag. TFT
Resolution: 1920 x 1080
Aspect Ratio: 16.9
Contrast Ratio: 2000:1
Response Time: 6 milliseconds
Display Colors: 16.7 million
Input Power: 100-240 VAC, 50-60Hz 4.0 A MAX
Operating Temp.: -24° to 122° F. (-31° to 50° C.)
Non-op. Temp.: -24° to 140° F. (-31° to 60° C.)
TV formats: 1080p, 1080i, 720p, 480p, 480i
Input: Antenna/CATV (ATSC/QAM/NTSC) x1
 HDMI™ with HDCP x2
 Component YPbPr plus stereo audio x2
 Composite video x 1, S-video x1
 L/R audio x1
 15-pin D-sub VGA plus Stereo Audio
 RS232 Serial
Audio: TosLink, 5.1 Audio from DTV input only
 (TosLink Optical) x1
Speaker: 10-Watt x 2 channels, water-resistant
 detachable speaker module
Dimensions: 44.72"W x 30.47"H (27.16"H without
 speaker module), x 6.85" D
Weight: 82.7 lbs., 86.8 lbs. with speaker module



Model 4610HD

Shown without Detachable Speaker Module

Control Set: RS232 serial
 Discrete IR control
 Concealed IR Window
Exterior: Powder-coated aluminum
Warranty: One-year, in-factory, parts and labor
Accessories Included: Water-resistant remote control with
 lithium battery

LCD Screen: 23" diag. TFT
Resolution: 1366 x 768
Aspect Ratio: 16.9
Contrast Ratio: 700:1
Response Time: 8 milliseconds
Display Colors: 16.7 million
Input Power: 100-240 VAC, 50-60Hz 2.2 A Max
Operating Temp.: -24° to 122° F. (-31° to 50° C.)
Non-op. Temp.: -24° to 140° F. (-31° to 60° C.)
TV formats: 1080i, 720p, 480p, 480i
Input: Antenna/CATV, (ATSC/QAM/NTSC),
 HDMI x 2/HDCP
 S-Video x1 and composite video x1,
 L/R Audio inputs x2
 YCbCr/YPbPr and audio L/R channels x2
 15-pin D-sub VGA plus stereo audio
 RS232 serial*
Audio: SPDIF Audio output, analog headphone jack
Speakers: 5-Watt x 2 channels, water-resistant
 built-in speakers
Dimensions: 23.51"W x 16.27"H x 4.9" D
Weight: 22 lbs.



Model 2310HD

Control Set: RS232 serial*
 Discrete IR control*
Exterior: Powder-coated aluminum
Warranty: One-year, in-factory, parts and labor
Accessories Included: Water-resistant remote control
 with lithium battery,
 Removable table-top stand

**Available only with Model 2310HD-Pro*



Model 3220HD

Shown with Detachable Speaker Module

Speaker: 10-Watt x 2 channels, water-resistant
 detachable speaker module
Control Set: RS232 serial
 Discrete IR control
 Concealed IR window
Exterior: Powder-coated aluminum
Dimensions: 32.07"W x 23.20"H (20.02"H without
 speaker module), x 6.29" D
Weight: 37.5 lbs., 41.6 lbs. with speaker module

Models 3220HD and 3230HD

LCD Screen: 31.5" diag. TFT
Resolution: 1366 x 768
Aspect Ratio: 16.9
Contrast Ratio: 1500:1
Response Time: 8 milliseconds
Display Colors: 16.7 million
Input Power: 100-240 VAC, 50-60Hz 2.5A MAX
Operating Temp.: -24° to 122° F. (-31° to 50° C.)
Non-op. Temp.: -24° to 140° F. (-31° to 60° C.)
TV formats: 1080i, 720p, 480i, 480p
Input: Antenna/CATV, (ATSC/NTSC/QAM),
 HDMI x 2, S-Video x1 and composite video x1,
 L/R audio inputs x2
 YCbCr/YPbPr and audio L/R channels x2
 15-pin D-sub VGA plus stereo audio
 RS232 serial (Model 3220HD only)
Audio: SPDIF audio output, analog headphone jack
Warranty: One-year, in-factory, parts and labor
Accessories Included: Water-resistant remote control with lithium
 battery; Removable table-top stand



Model 3230HD

Speakers: 10-Watt x 2 channels, water-resistant built-in speakers
Exterior: Outdoor-rated ASA plastic resin
Dimensions: 32.21"W x 23.21"H x 6.97" D
Weight: 39 lbs.


www.sunbritev.com