



Technical Data

13 Amp Power Socket with USB Charger


Brief product description:

The BG Electrical Part M range offers a wide range of suitable solutions to enable compliance to the requirements of Part M1 (Sections 4.25-4.29) with contrasting colours and sleek polycarbonate front plates.

Features:

- Slim and sleek polycarbonate front plate
- 13A Power Sockets with integrated USB-A ports
- Smart Charging - Intelligently adjusts the voltage to give devices the power they need, when they need it, without overcharging
- Easy to install, supplied with fixing screws and installation instructions
- Angled in-line colour coded terminals with backed out screws for fast installation
- Twin earth fitted as standard for high integrity circuits
- Contrasting graphite and white design to aid the visually impaired
- Part M approved

Product Images



PM22U3

Technical Specifications


Standard(s)	BS 1363-2:2016+A1:2018
Rating	13A 240V AC
Contact Gap	3.0mm minimum
Switch Type	Single Pole
USB Output	5V, 3.1A, shared across two USB ports
Output Tolerance	<5%
Standby Power	<75mW
USB Overcurrent Protection	≤3.60A
Terminal Capacity	3 x 2.5mm ² , 3 x 4.0mm ² & 2 x 6.0mm ²
Light Reflective Value	8.9
RoHS Directive	Yes
WEEE Directive	Yes
Mounting Box Depth (Min)	25mm
Fixing Centres	120.6mm





13 Amp Power Socket with USB Charger

Line Diagrams



PM22U3

Packaging Information

Cat No.	Description	Packaging Type			Pack Quantity			Barcode		
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box
PM22U3	2G, 2 x USB (3.1A)	Printed Bag	Printed Carton	Printed Carton	1	5	50	5050765199797	5050765199803	5050765199810

Weights & Dimensions

Cat No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m ³)
		Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
PM22U3	2G, 2 x USB (3.1A)	8.6 x 14.6 x 3.2	19.5 x 12.5 x 3.3	9.7 x 16.2 x 17.7	19.6 x 33.3 x 50.3	0.164	0.169	0.92	9.52	0.03283