

TrueSky

Product Features

- Dynamic Sky: Clouds can move and change dynamically
- Sky linkage: Multiple Ewindows can be spliced together, and the sky can be dynamically linked
- 24 Hour Sunlight: Simulate 24-hour changes in sunlight, morning, noon, dusk, and starry sky
- Sunlight spectrum: Simulate the sunlight spectrum, with a similarity of 90% to sunlight



CAT NO.	DRIVER	WATTAGE	CUTOUT
LTS1212	Fixed Output	415W	1195 x 1195mm
LTS1206	Fixed Output	240W	1195 x 595mm

PRODUCT ACCESSORIES

TrueSky Switchplate	LTSSW
---------------------	-------

CAT NO.	WEIGHT (kg)	CRI	FREQUENCY (Hz)	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)	L/B RATED LIFE
LTS1212	40	>98	50-60	-20 - +40	25	L70/B50
LTS1206	20	>98	50-60	-20 - +40	25	L70/B50

STANDARD	DESCRIPTION
EN 60598-1	Luminaires – General requirements
EN 60598-2-1	Luminaires – Fixed general purpose
EN 61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions
EN 61000-3-3	Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
EN 61547	Equipment for general lighting purposes – EMC immunity requirements
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

