

LUXPANEL EXTRA 1200 x 600

Product Features

- Backlit LED Panel with slimline 30mm depth finished in RAL9016 white
- Plug and play ENEC approved loop in-out driver with power change dip switch on fixed output versions
- 1200x600mm white aluminium frame with TPa rated diffuser and UGR19 compliant
- Recessed mounted suitable for use in 15mm or 24mm standard exposed ceiling grids
- Rear safety wire suspension points as standard



Upon request



LUCECO
PLATFORM
WIRELESS LIGHTING CONTROLS

CAT NO.	DRIVER	LUMINAIRE LUMENS	WATTAGE	lm/W
LBX612WS40	Fixed Output	4250 / 5000	27 / 32W	157 / 156
LBX612W42D40	Digital Dimmable	4250	27W	157
LBX612W50D40	Digital Dimmable	5000	32W	156

To Specify:

Recessed Luxpanel Extra 1200x600mm LED Panel with efficacy up to 157lm/cw, UGR19 and TPa rated diffuser.


PRODUCT ACCESSORIES

1200x600 Surface Mounting Frame	LPF612W
1200x600 Plasterboard Recessing Frame	LPF612SCRF
4 point 1.5 Metre Suspension Kit	EBPWSK415

PRODUCT OPTIONS

Luceco 3 Hour Remote Emergency Pack	LED3EP1004W
Self-Test Emergency Pack	LED3EP1004W
DALI Addressable Emergency Pack	LED3EP80DED
Luceco Platform Wireless – insert LPW	LBX612W50LPW40

Product Drawing



CAT NO.	WEIGHT	CRI	VOLTAGE	FREQUENCY (Hz)	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)
LBX612WS40						
LBX612W42D40	3.6kg	>80	220-240V	50-60	-20° - +25°	25
LBX612W50D40						

LBX612WS40

Luminaire Performance

Luminaire Efficiency: **100%**


Luminaire Efficacy: **139 lm/W**

Classification: **A50 ±99.6% ±0.4%**

CIE Flux Codes: **60 87 97 100 100**

UGR 4H 8H
(20%, 50%, 70%) **16.4 / 15.6**
CO / C90:

Luminous Intensity



STANDARD	DESCRIPTION
EN 60598-1	Luminaires – General requirements
EN 60598-2-2	Luminaires – Recessed
EN 60598-2-22	Luminaires – Emergency
EN 61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions
EN 61000-3-3	Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
EN 61547	Equipment for general lighting purposes – EMC immunity requirements
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment



RoHS

