

LED T8 TUBES




Product Features

- Up to 115lm/W - energy saving against fluorescent for similar lux levels.
- Retrofit with most T8 luminaires (non dimming)
- Shorted end, supplied with dummy replacement LED starter
- Fragment retention PET film



CAT NO.	COLOUR TEMPERATURE	LUMINAIRE LUMENS	WATTAGE	LENGTH
LT8G2N9W11	4000K	1030	9W	600mm/2FT
LT8G2C9W11	6500K	1030	9W	600mm/2FT
LT8G4N18W20	4000K	2070	18W	1200mm/4FT
LT8G4C18W20	6500K	2070	18W	1200mm/4FT
LT8G5N23W35	4000K	3500	23W	1500mm/5FT
LT8G5C23W35	6500K	3500	23W	1500mm/5FT
LT8G6N36W41	4000K	4140	36W	1800mm/6FT
LT8G6C36W41	6500K	4140	36W	1800mm/6FT

Product Drawing



CAT NO.	WEIGHT (kg)	EFFICACY (lm/w)	CRI	FREQUENCY (Hz)	SWITCHING CYCLE	AMBIENT TEMP RATED LIFE (°C)	L/B RATED LIFE
LT8G2N9W11	0.104	114	>80	50-60	15,000	25	L70 / B50
LT8G2C9W11	0.104	114	>80	50-60	15,000	25	L70 / B50
LT8G4N18W20	0.2	115	>80	50-60	15,000	25	L70 / B50
LT8G4C18W20	0.2	115	>80	50-60	15,000	25	L70 / B50
LT8G5N23W35	0.25	152	>80	50-60	15,000	25	L70 / B50
LT8G5C23W35	0.25	152	>80	50-60	15,000	25	L70 / B50
LT8G6N36W41	0.4	115	>80	50-60	15,000	25	L70 / B50
LT8G6C36W41	0.4	115	>80	50-60	15,000	25	L70 / B50

STANDARD	DESCRIPTION
60598-1	Luminaires – General requirements
61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions
61000-3-3	Lamp controlgear – Part 1: General and safety requirements
61547	Equipment for general lighting purposes – EMC immunity requirements
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

ENERGY
Luceco
LT8G4C18W20
A
B
C
D
E
F
G
18
kWh/1000h
2019/2015

