

## **TEMPUS PROFILE EXIT BOX**

## **Product Features**

- · Wall mounted maintained exit box
- · Steel body construction with polycarbonate legend
- · Above and rear cable entry points
- · Supplied with UP legend as standard other directions can be supplied as accessories
















CAT NO.	TYPE	LEGEND DIRECTION	WATTAGE
LTPEBXM3	Maintained	Up	3W

## **Product Accessories**

CAT NO.	LEGEND DIRECTION	
LTPEBXDA	Downward Legend	
LTPEBXRA	Right Legend	
LTPEBXLA	Left Legend	

## **Product Drawing**



CAT NO.	WEIGHT (Kg)	CRI	FREQUENCY (Hz)	IK RATING	BATTERY TYPE	BATTERY CAPACITY	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)	
LTPEBXM3	1.45	≥80	50-60	IK04	Ni-Cd 3.6V	1500mAh	-5 - +40	25	

STANDARD	DESCRIPTION		
60598-1	Luminaires – General requirements		
60598-2-22	Luminaires – Emergency		
61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits – for harmonic current emissions		
61000-3-3	Lamp controlgear – Part 1: General and safety requirements		
61547	Equipment for general lighting purposes – EMC immunity requirements		
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment		

