

# **Technical Data**

# Weatherproof 13 Amp Switched Fused Connection Unit

#### **Brief product description:**

IP rated accessories designed to protect against ingress from water jets and dust, with durable seals that maintain integrity and a robust polycarbonate housing for high impact resistance which will not crack or fade, ensuring longevity of life.

## Features:


- IP55 rated when in use
- Hinged cover provides access to the fuse
- Angled colour coded terminals with captive screws
- M20 + M25 knock-outs in supplied mounting box


### Product Images



WPB50

#### Line Diagrams







WPB50



Technical Specifications		
Standard(s)	BS EN 60669-1	— <b>( €</b> ੫ĸ
Rating	13 Amp 250V AC	
Terminal Capacity	4 x 1.0mm² 4 x 1.5mm² 2 x 2.5mm² 1 x 4.0mm²	
Switch Type	Double Pole	
IP Rating	IP55	
RoHS Directive	Yes	
WEEE Directive	Yes	
Number of cable entries	4 x 20mm. 1 in each side	
	1 drill out entry 20/25mm in rear face	

Packaging Information											
Cat No.	Description	Packaging Type			Pack Quantity			Barcode			
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box	
WPB50	Switched FCU	Printed Box	Carton	Carton	1	10	100	5050765037365	5050765037457	5050765037549	

Weights & Dimensions											
	Cat No.	Description	D	imensions	(H x W x D)	Weight (kg)				CBM (m <sup>3</sup> )	
			Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
	WPB50	Switched FCU	9.1 x 7.5 x 6.4	11.2 x 7.6 x 6.5	10.3 x 16.2 x 34.7	37.5 x 36.5 x 53	0.16	0.19	1.87	19.17	0.07254

British General Helpline 03300 249 279

Supplied by Luceco PLC Stafford Park 1 Telford TF3 3BD ENGLAND

Visit our website at **www.bgelectrical.uk**