

LUXBAY | ULTRA

High specification LED luminaire designed for use in "Super Shed" distribution centres. Optimal spacing for high level & racking applications.

Product Features

- High performance specialist luminaire designed specifically for high level industrial applications
- Range of outputs up to 46000 lumens and efficacy up to 180Lm/cW
- Aluminium housing and polycarbonate lenses with each lens type specially designed to maximise spacings on install
- Number of mounting options to fit all installations including surface mount, suspended and busbar trunking systems
- Wireless lighting control available via Luceco Platform and Elevate Systems



CAT NO.	TYPE	DRIVER	LUMINAIRE LUMENS	WATTAGE	Lm/W
LLU09WLL22S40	Low Level	Fixed Output	22000	122	180
LLU09WLL22E40	Low Level	Emergency	22000	122	180
LLU09WHL22S40	High Level	Fixed Output	22000	122	180
LLU09WHL22E40	High Level	Emergency	22000	122	180
LLU09WR21S40	Racking	Fixed Output	21000	122	172
LLU09WR21E40	Racking	Emergency	21000	122	172
LLU12WLL36S40	Low Level	Fixed Output	36000	215	167
LLU12WLL36E40	Low Level	Emergency	36000	215	167
LLU12WHL36S40	High Level	Fixed Output	36000	215	167
LLU12WHL36E40	High Level	Emergency	36000	215	167
LLU12WR34S40	Racking	Fixed Output	34000	215	158
LLU12WR34E40	Racking	Emergency	34000	215	158
LLU15WLL46S40	Low Level	Fixed Output	46000	270	170
LLU15WLL46E40	Low Level	Emergency	46000	270	170
LLU15WHL46S40	High Level	Fixed Output	46000	270	170
LLU15WHL46E40	High Level	Emergency	46000	270	170
LLU15WR44S40	Racking	Fixed Output	44000	270	163
LLU15WR44E40	Racking	Emergency	44000	270	163

To Specify:

Surface, suspended or busbar trunking mounted high performance LED luminaire, efficacy up to 180Lm/cW. Lens options for low or high level performance and racking applications.

Product Drawing

