

Ceiling & Lighting

ACCESSORIES





www.bgelectrical.uk



138

Ceiling & Lighting Accessories

High quality and robust accessories offering durability, reliability and ease of installation.

Our products combine modern styling with ease of use for installers, and are manufactured to high quality and reliability standards. The extensive range includes; ceiling roses, pendant sets, batten holders and fluorescent starters and all the technical information.

IN THE RANGE	
Ceiling Roses	140
Pendant Sets	140
Batten Holders	140
Ceiling Switches	141
Lamp Holders	141
Luminaire Connectors	142
Fluorescent Starters	142



BG Electrical products are guaranteed against faulty materials and workmanship for a period of 25 years from date of delivery.

Features & Finishes







Ceiling Roses

· Large capacity earth terminal with locking terminal screw · Eight "in-line" terminals all with captive screws Wiring aperture in base with extra knockout for ease of wiring Spin-on cover with smooth cable entry for maximum protection of pendant conductor insulation Large capacity earth terminal with locking terminal screw Base moulded in clear polycarbonate Cover moulded in satin finish urea Manufactured to BS67



Product Code	Description	Inner Carton	Outer Carton
561	3.5" diameter	10	100
661	3" diameter	10	100

Pendant Sets (T2)

Product

Code

566

748

140

· Large capacity earth terminal with locking terminal screw · Wiring aperture in base with extra knockout for ease of wiring 0.75mm pendant flex heat resistant to BS6141 Spin-on cover with smooth cable entry for maximum protection of pendant conductor insulation · Eight "in-line" terminals all with captive screws · Manufactured to BS67 and BS EN 60598-2-1

Description

6" flex and 3.5" base

Batten Holders Enclosed (T2)

Diameter of batten lampholder is 80mm (3")

· Large capacity earth terminal with locking terminal screw



767



Product Code	Description	Inner Carton	Outer Carton
763	2 terminal body, 3 terminals + earth in base, PVC tails, HO skirt	10	100
767	2 terminal body angled, 3 terminals + earth in base and PVC tails, HO skirt	10	100

Batten	Holders (T2)				
 Knock-o 3 Termin 	tured to BS EN 61184 uts to allow for surface wiring als bayonet cap lamps Description	Inner Carton	Outer Carton		Ð,
				753	748
752	3 terminals with short skirt	10	100		
753	3 terminals with HO skirt	10	100		
747	3 terminal angled with HO skirt	10	100		

100

10

Outer

Carton

100

100

100

100

100

100

Inner

Carton

10

10

10

10

10

10

Ceiling Switches

 Supplied with approximately 1.5 metres of cord Individually bagged
 Manufactured to BS EN 60669-01

Product Code	Description	Inner Carton	Outer Carton
801	6 Amp 1 way	10	100
802	6 Amp 2 way	10	100
803	45 Amp double pole with power indicator	10	100
804	10 Amp triple pole fan isolator	10	100
801PC	Replacement pull cord, 1.5m	20	200



Decorative Ceiling Roses and Switches

- · Supplied with approximately 1.5 metres of cord
- Individually bagged
- · Manufactured to BS EN 60669-01

Product Code	Description	Inner Carton	Outer Carton
802CH	6 Amp 2 way ceiling switch chrome finish	5	50
802ST	6 Amp 2 way ceiling switch steel finish	5	50
661CH	Chrome finish cover with polycarbonate 3" diameter base	5	50
661ST	Steel finish cover with polycarbonate 3" diameter base	5	50



Lamp Holders – Heat Resistant (T2)

•	Moulded in robust fully insulating plastic
•	Positive cord-grip
•	Manufactured to BS EN 61184
•	2A at 250V AC

Product Code	Description	Inner Carton	Outer Carton
720	Cord grip with short skirt	20	20
721	Cord grip with HO skirt	20	20
725	1/2"/12.6mm 26 BSB threaded entry with short skirt	20	20
252	Pushbar lamp holder switched $\ensuremath{\mathscr{V}}\xspace^{\prime\prime}$ 26 BSB with threaded entry and short skirt	20	20
7369	HO skirt	100	1000



Ceiling & Lighting | Accessories

Pendant Set – Edison Screw

- Large capacity earth terminal with locking terminal screw
- · Wiring aperture in the base with extra knockout for ease of wiring
- · Base incorporates L, N and loop-in terminals with 8 individual cable entries and captive screws
- Spin-on-cover with smooth cable entry for maximum protection of pendant
- conductor insulation
- Alternative fixing holes allow for off centre mounting
- 0.75mm² two core circular cable
- · Lamp holder pre-wired to cable ready to be fitted to ceiling rose
- 6"/15cm flex & 3"/80mm diameter base

Product Code	Description	Inner Carton	Outer Carton
666ES14	Pendant set – E14 Edison screw	10	100
666ES27	Pendant set – E27 Edison screw	10	100



3 terminal angled with short skirt

Luminaire Support Connector

Description

Product Code

LSC4PA/4C2

LSC4PA/4C3

LSCPLG/RD

LSC4PA

LSCPLG

• The 6A plug-in ceiling rose offers a pluggable connection for luminaires The luminaire can be connected and disconnected under load · Plug and sockets have 4 terminations for live, neutral, earth and loop-in Supports up to 5kg load · Moulded in durable PC matt plastic material · Cables have prepared ends

Luminaire support connector 4 pin plug + socket 2M 4C 0.75mm cable

Luminaire support connector 4 pin plug + socket 3M 4C 0.75mm cable

Luminaire support connector 4 pin plug + socket assembly

Luminaire support connector 4 pin plug - red

Luminaire support connector 4 pin plug



I SC4PA/4C3



Outer

Carton 100

100

100

100

100

Inner

Carton

10

10

10

10

10

Fluorescent Starter Specifications

Lamp Type	Wattage	Circuit	FSU	FS125	FS2
150mm	4 W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
225mm	6W	Single	220/250V	-	110/130V
	-	Twin Series	-	-	220/250V
300mm	8W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
525mm	13W	Single	220/250V	-	-
450mm	15W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
360mm	16W	Single	220/250V	-	110/130V
600mm	18/20W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
Circline	22W	Single	220/250V	-	110/130V
900mm	30W	Single	220/250V	-	-
Circline	32W	Single	220/250V	-	-
600mm	40W	Single	220/250V	-	-
1200mm	36/40W	Single	220/250V	-	-
1500mm	85/80W	Single	220/250V	240/250V	-
1800mm	70/85W	Single	220/250V	240/250V	-
2400mm	100/125W	Single	-	240/250V	-



BG GENERAL torm

BRITISH

WEATHERPROOF WIRING ACCESSORIES -----

BG Weatherproof Range The preferred choice of the nation's contractors for over 10 years



An evolution in weatherproof switches & sockets

The best just got better...

Now even easier to install and operate

- Fast-fix no separate screws, no screw covers, 150° rotation
- Quick release socket plate with 1/4 turn fixing for easier installation
- · Patented cable entry prevents accidental opening of the cover
- · Redesigned paddles with smoother operation, for easier use
- · Additional sealant channels to prevent water ingress
- · Improved internal seals over fixing points

BG

LUCECO



SYNC J LUCEC



nexus

ROSS

www.**bg-storm**.uk

Kingfisher

Lighting

DIF DW Wind

Windsor



BG



UK: HEAD OFFICE: Email: info@bgelectrical.uk

Luceco plc, Caparo House 103 Baker Street, London England, W1U 6LN

DISTRIBUTION CENTRE:

Tel: +44 (0) 1952 238 100 Email: uk_sales@bgelectrical.uk

Luceco plc Luceco Distribution Centre Stafford Park 1, Telford Shropshire, England, TF3 3BD

FRANCE:

Email: fr_sales@luceco.com

ITALY: Email: it_sales@luceco.com

SPAIN:

Tel: +34 93 829 55 75 Email: es_sales@luceco.com

Nexus Industries LTD C/ Bobinadora 1-5 08302 Mataró Barcelona (SPAIN)

MIDDLE EAST & AFRICA:

Tel: +971 4 609 1867 Email: mea_sales@luceco.com

Luceco Middle East FZCO Bldg. 5EB, Office 342 PO Box 371128, DAFZA Dubai, UAE

ASIA PACIFIC: JIAXING:

Tel: +86 (0) 573 8357 0200 Email: asia_sales@luceco.com

No 1438, Jiachuang Road Xiuzhou Industrial Park, Jiaxing Zhejiang, China, P.C. 314031

HONG KONG: Email: hk_sales@luceco.com

UNITED STATES: Email: us_sales@luceco.com

MEXICO & LATIN AMERICA:

Tel: +52 (81) 5000 9437 Email: ventas@luceco.com

Luceco México AV Lāzano Cārdenas #318 int 201 Col Real San Agustin San Pedro Garza Garcia N.L. Mexico CP 66278

TECHNICAL SUPPORT:

Tel: 03300 249 279 Email: technical.support@bg-electrical.co.uk

> DW Windsor

nexus

ROSS

Kingfisher Liahtina

Lines open Monday to Friday 8.30am to 5pm, with answer phone service outside these hours.



BG

<u>LUCE</u>C©

SYNC (=V) LUCECO