

110V TRIPOD WORK LIGHT



Product Features

- Robust aluminium tripod and LED heads
- Supplied with toughened glass for onsite applications
- Supplied with 300mm 3 core rubber cable 110V 16A plug to EN 60309



CAT NO.	TYPE	LUMINAIRE LUMENS	WATTAGE
LSLSTW201V	Single Head	2000	20W
LSLTTW2201V	Twin Head	2 x 2000	2 x 20W

CAT NO.	WEIGHT (kg)	CRI	FREQUENCY	IK RATING	CABLE TYPE	CABLE LENGTH	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)
LSLSTW201V	2.32	>80	50-60	IK08	H07RN-F 1.0mm ²	3000mm	-20 +25	25
LSLTTW2201V	3.27	>80	50-60	IK08	H07RN-F 1.0mm ²	3000mm	-20 +25	25



STANDARD	DESCRIPTION
60598-1	Luminaires – General requirements
60598-2-4	Luminaires – Portable
61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits – for harmonic current emissions
61000-3-3	Lamp controlgear – Part 1: General and safety requirements
61547	Equipment for general lighting purposes – EMC immunity requirements
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

