

Technical Data

25 Amp Flex Outlet Plate

Brief product description:

A standard range of white moulded wall accessories offering superb quality and exceptional value.

Features:

- White moulded square edge profile offering exceptional value
- Easy to install, supplied with fixing screws and installation instructions
- Twin Earth for high integrity circuits
- Cable entry in lower edge with removable reducer and reversible cord grip
- Angled terminals with captive, backed out screws for fast installation
- Screw cover caps for a sleek appearance
- Anti-microbial certified manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

Product Images




954

Technical Specifications Standard(s) BS 5733 25 Amp 250V AC Rating 2 x 2.5mm² 1 x 4.0mm² **Terminal Capacity RoHS** Directive Yes WEEE Directive Yes Mounting Box Depth (Min) 25mm 60.3mm **Fixing Centres**



25 Amp Flex Outlet Plate

Line Diagrams



Packaging Information

Cat No.	Description	Packaging Type			Pack Quantity			Barcode			
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box	
954	FLEX OUTLET PLATE	Printed Bag	Printed Carton	Printed Carton	1	10	100	5021166954001	5021166954094	5021166954087	

Weights & Dimensions

Cat No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m ³)
		Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
954	FLEX OUTLET PLATE	8.6 x 8.6 x 2.7	14.4 x 13.1 x 2.8	9.5 x 12.7 x 18.2	20.1 x 26.3 x 50.3	0.097	0.101	1.03	10.94	0.02659

British General Helpline 03300 249 279