

Technical Data Metal Enclosures

Description:

Enclosures are typically used as an extension to an existing consumer unit but can also be used in isolation. Typical applications include house and loft extensions, garages, sheds, workshops or for showers.

This range of all metal enclosures are manufactured from steel and are compliant with the 18th Edition Wiring Regulations, BS7671. Enclosure kits are supplied complete with devices, DIN rail, neutral cable, neutral and earth terminals and a busbar.

Cover blanks are supplied to allow the installation of single pole RCBOs or single pole SPDs.

M20 knockouts can be drilled to M32 if required with a range of cable glands and grommet kits also available to maintain IP ratings.






| Specification CFUE4M | | CFUGAR1A | CFUGAR2 | CFUSHOW1A | | | | | |
|------------------------|-------------------|---------------------|------------------|---------------------|--|--|--|--|--|
| Standard (s) | | EN / IEC 61439 | | | | | | | |
| Populated | No | Yes | Yes | Yes | | | | | |
| Incomer | N/A | 40A 30mA Type A RCD | 100A Main Switch | 63A 30mA Type A RCE | | | | | |
| No of MCBs | 0 | 1x 6A | 1x 6A | 1x 50A | | | | | |
| | | 1x 32A | 1x 16A | | | | | | |
| No of Modules | | 4 | | | | | | | |
| Max No of Ways after | ncomer | 3 | | | | | | | |
| Material | • | | | | | | | | |
| Finish | White gloss | | | | | | | | |
| UV Stability | | | | | | | | | |
| Cover Blanks | | 1 | | | | | | | |
| IP Rating | | IP20 | | | | | | | |
| | | | | | | | | | |
| Cut Outs & Knockouts | } | | | | | | | | |
| Туре | | | | | | | | | |
| M20 | Top & Bottom Face | Sides | Base | | | | | | |
| M32 | 3 | 2 | 1 | | | | | | |
| Oval | | | | | | | | | |

Metal Enclosures

Line Diagrams



Enclosure Sizes & Weights

| Cat No. | D | Fixing Centres (mm) | | | Product Weight | | | |
|-----------|-------|---------------------|-------|----|----------------|------|------|--|
| | Χ | Y | Depth | X1 | Y1 | Z | Kg | |
| CFUE4M | 172.4 | 234.5 | 115 | 85 | 160 | ø5.5 | 1.56 | |
| CFUGAR1A | 172.4 | 234.5 | 115 | 85 | 160 | ø5.5 | 2.00 | |
| CFUGAR2 | 172.4 | 234.5 | 115 | 85 | 160 | ø5.5 | 2.00 | |
| CFUSHOW1A | 172.4 | 234.5 | 115 | 85 | 160 | ø5.5 | 1.96 | |

Packaging Information

| Cat No. | Description | Packaging Type | | | Pack Quantity | | | Barcode | | |
|-----------|-------------------|----------------|--------------|--------------|---------------|--------------|--------------|---------------|--------------|---------------|
| | | Product | Inner Box | Outer Box | Each | Inner Box | Outer Box | Individual | Inner Box | Outer Box |
| CFUE4M | Empty enclosure | Box | - | Carton | 1 | - | 6 | 5050765147224 | - | 5050765155151 |
| CFUGAR1A | Garage kit - IP20 | Box | - | Carton | 1 | - | 6 | 5050765229739 | - | 5050765229746 |
| CFUGAR2 | Garage kit - IP20 | Box | - | Carton | 1 | - | 6 | 5050765147248 | - | 5050765155175 |
| CFUSHOW1A | Shower Kit - IP20 | Box | - | Carton | 1 | - | 6 | 5050765229753 | - | 5050765229760 |

Installation Information

Safety Warning

Before use please read and carefully use in accordance with these safety wiring instructions.

To ensure a satisfactory operation these products should be installed by a competent person. If in doubt seek advice from a qualified engineer.

Technical Helpline: 03300 249 279
If in doubt consult a competent electrician.