

AZURAR GU10 SPIKE LIGHT

- GU10 stainless steel constructed garden spike light with tempered glass
- · 1.95m pre-wired H05RN cable
- Range of colour finishing available perfect for all residential installation in outdoor spaces including exterior walkways, garden and communal patios areas











CAT NO.	FINISH
LEXDLSSS	Stainless steel
LEXDLSBK	Black
LEXDLSCP	Copper




Range of colour finishing







Product Drawing



Suitable for GU10 lamps (Lamp not included)







CAT NO.	LAMP BASE	WEIGHT (kg)	WATTAGE (W)	INPUT VOLTAGE (V)	FREQUENCY (Hz)	LIFESPAN (Hrs)	IP RATING
LEXDLSSS	GU10	0.555	2x35	230	50	25,000	IP54
LEXDLSBK	GU10	0.555	2x35	230	50	25,000	IP54
LEXDLSCP	GU10	0.555	2x35	230	50	25,000	IP54

STANDARD	DESCRIPTION			
EN 60598-1	Luminaires – General requirements			
EN 60598-2-1	Luminaires – Fixed general purpose			
EN 61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits - for harmonic current emissions			
EN 61000-3-3	Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection			
EN 61547	Equipment for general lighting purposes – EMC immunity requirements			
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment			













