

Technical Data

13 Amp Type A RCD Fused Connection Unit

Brief product description:


The subtle design will blend with any décor - suitable for domestic or commercial installations.

Features:

- White moulded round edge, sleek and slim with softly rounded edges
- Integrated Type A RCD to prevent the leakage of electrical current
- Easy to install, supplied with fixing screws and installation instructions
- Colour coded terminals with backed out captive screws for fast installation
- Screw cover caps for a sleek appearance
- Twin earth fitted as standard
- Anti-microbial certified manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

Product Images






855ARCD

Technical Specifications		
Standard(s)	BS 7288: 1990	UK
Rating	13 Amp	CA
Maximum Load	3120 Watts, 240V A	(f
RCD Rating	30mA, Trip speed 40 ms	
RCD Type	Latching Type	
Terminal Capacity	4 x 1.0mm², 4 x 1.5mm², 2 x 2.5mm² & 1 x 4.0mm²	
RoHS Directive	Yes	
WEEE Directive	Yes	
Mounting Box Depth (Min)	35mm, 10mm spacer provided for shallower boxes	
Fixing Centres	60.3mm	



13 Amp Type A RCD Fused Connection Unit

Line Diagrams



Packaging Information

Cat No.	Description	Packaging Type			Pack Quantity			Barcode			
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box	
855ARCD	13A TYPE A RCD FCU	Printed Bag	Printed Carton	Printed Carton	1	10	100	5050765236140	5050765236157	5050765236164	

Weights & Dimensions										
Cat No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m ³)
		Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
855ARCD	13A TYPE A RCD FCU	8.6 x 8.6 x 3.8	17.0 x 12.0 x 4.0	9.7 x 18.7 x 20.2	22.1 x 38.3 x 50.3	0.153	0.157	1.66	17.11	0.04258

British General Helpline 03300 249 279