

Technical Data

Double 13 Amp Power Socket with 22W Type C USB

Brief product description:

The BG Screwless Flatplate range has a slimline design with a clip on/off front plate for a sleek and screwless finish.

The faceplates are simple to remove when decorating for a practical and convenient solution.

This innovative power socket with integrated 'fast charge' USB-A and USB-C ports can replace any standard socket - a neat solution with no loss of valuable power sockets.

Features:

- 13A Power Sockets with integrated 'fast charge' USB-A & USB-C ports.
- Supports PD and QC charging protocols and outputs the best voltage & current for optimum charging.
- Smart Charging Intelligently adjusts the voltage to give devices the power they need, when they need it, without overcharging.
- Compatible with all smartphone brands including Apple, Samsung, Google and Huawei.
- Screwless front plate clips on and off easily and has a sleek flat profile.
- Moisture control gasket prevents tarnishing from new plaster.
- Angled, colour coded terminals with captive screws.
- Twin earth for high integrity circuits.
- Minimum mounting box depth: 25mm

Product Images









Technical Specifications		
Standard(s)	BS 1363-2:2016+A1:2018, BS EN 62368-1:2014, EN55032	UK
Rating	13 Amp 240V ~	CA
Contact Gap	3.0mm minimum	-
Switch Type	Single Pole	
Terminal Capacity - L & N	3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²	A\$A
RoHS Directive	Yes	Intertek
WEEE Directive	Yes	Lic No.1182
Mounting Box Depth (Min)	25mm	
Fixing Centres	120.6mm	



Double 13 Amp Power Socket with 22W Type C USB

Electrical Specification						
Input Requirement	Input voltage range	200-240Vac±10%				
	Input frequency range	50/60Hz				
	Input current	1A Max				
	Turn on delay time	<1S				
Input Protection	Input current protection	2A Fuse				
USB C Output	Output power	21.6W max				
	Output	5V/3A; 9/2.4A; 12V/1.5A; 15V/1.4A; 20V/1A				
	Charge protocols	PD3.0; QC3.0; Apple2.4A; Sumsung 2.0;				
		Samsung AFC; Huawei FCP; BC1.2				
USB A Output	Output power	21.6W max				
-	Output	5V/3A; 9V/2.4A; 12V/1.5A				
	Charge protocols	QC3.0; Apple2.4A; Samsung2.0A;				
		Samsung AFC; Huawei FCP; BC1.2				
If both USB-C and USB-A are plug	gged in	USB-C Support 12W (5V/2.4A);				
		USB-A Support 12W (5V/2.4A);				
Protection	DC Output Over Current Protection	Recover automatically				
	DC Output Over Voltage Protection	Recover automatically				
	Reset After Shutdown	Yes				
	Over-temperature protection	Yes				
Standards & Safety Certification	CE ASTA	BS 1363-2:2016+A1:2018				
		EN 62368-1:2020+A11:2020				
	CE EMC	EN 6100-6-1:2019				
		EN6100-6-3:2021				
	EMI	EN55032				
	HI-POT test	<5mA/4000V/60S				

Line Diagrams





FFB22UAC22B 2G USB A+C 22W Eco Blister Printed Box Printed Box 1

F**22UAC22*

Packaging Information											
Cat No.	Description	Packaging Type			Pack Quantity			Barcode			
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box	

Weights & Dimensions										
Cat No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m³)
		Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
F**22UAC22*	2G USB A+C 22W	8.6 x 14.7 x 3.2	15.3 x 18 x 3.6	18.8 x 12.7 x 20.8	21.9 x 38.5 x 64.8	0.289	0.325	1.71	17.66	0.05464

British General Helpline

Supplied by

Luceco PLC Stafford Park 1 Telford TF3 3BD ENGLAND Visit our website at

www.bgelectrical.uk

5050765251020 5050765253161 5050765253178