

Technical Data

Weatherproof Type A RCD Protected FCU

Brief product description:

IP rated accessories designed to protect against ingress from water jets and dust, with durable seals that maintain integrity and a robust polycarbonate housing for high impact resistance which will not crack or fade, ensuring longevity of life.

Features:


- IP66 rated when in use
- Type A RCD protection: Cuts off power safely & prevents electrocution in event of a fault 30mA trip current & 40ms trip circuit operation.
- Latching operation: socket returns to original state when power is resumed
- Angled colour coded terminals with captive screws
- Flexible membrane: Allows easy switch and power status indication without compromising IP rating
- Hinged cover with fixing screw provides access to the fuse
- Fast fix no separate screws, no screw covers, 150° rotation
- Multiple gland entry positions: 5 versatile entry options with M25 capability with an easy push out blank plug design. 1 drill out entry 20/25mm in rear face

Product Images



WP55ARCD

Line Diagrams



WP55ARCD



0

| Technical Specifications | | | | | |
|-------------------------------|--|--|--|--|--|
| Standard(s) | BS7288 | | | | |
| Rating | 13 Amp 250V AC | | | | |
| Max Load | 3,120 Watts | | | | |
| RCD Mechanism – Latching (Pas | sive) socket returns to original state when power is resumed | | | | |
| RCD Type | A | | | | |
| Trip Current | 30mA, 40mS trip speed | | | | |
| Terminal Capacity | 3 x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² | | | | |
| IP Rating | IP66 | | | | |
| RoHS Directive | Yes | | | | |
| WEEE Directive | Yes | | | | |
| Number of cable entries | 5 x 20mm. 1 in each of 3 sides and 2 in the remaining side 1 drill out entry | | | | |
| | 20/25mm in rear face | | | | |

| Packaging Information | | | | | | | | | | | |
|-----------------------|----------------------------|-------------|---------------|-----------|------|--------------|--------------|---------------|-----------|---------------|--|
| Cat No. | Description Packaging Type | | Pack Quantity | | | Barcode | | | | | |
| | | Product | Inner Box | Outer Box | Each | Inner Box | Outer Box | Individual | Inner Box | Outer Box | |
| WP55ARCD | RCD Type A FCU | Printed Box | / | Carton | 1 | / | 10 | 5050765236201 | - | 5050765236218 | |

| weights & Dimensions | | | | | | | | | | | |
|----------------------|----------------|---------------------|-------------------|--------------------|---------------------|-----------------------|--------------|-----------|--|--|--|
| Cat No. | Description | Dime | nsions (H x W x I | D) cm | | CBM (m ³) | | | | | |
| | | Unpacked Product | Packed Product | Outer Box | Unpacked Product | Packed Product | Outer Box | Outer Box | | | |
| WP55ARCD | RCD Type A FCU | 11.5 x 11.5 x 6.3 | 14.7 x 12.2 x 7.2 | 13.6 x 28.3 x 37.3 | 0.38 | 0.43 | 4.55 | 0.01436 | | | |

British General Helpline 03300 249 279